

# The `latex-lab-math` code\*

Frank Mittelbach, Joseph Wright, L<sup>A</sup>T<sub>E</sub>X Project

v0.6c 2024-08-22

## Abstract

This is an experimental prototype. It captures math material (basically okay, but the interfaces for packages aren't yet there) and tags the material (which is not yet anywhere near the final state). That part is provided for experimentation and to gather feedback, etc.

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Math capture</b>	<b>3</b>
2.1	Code level interfaces . . . . .	3
2.2	Document level interfaces . . . . .	3
<b>3</b>	<b>Math tagging</b>	<b>3</b>
3.1	Inline math . . . . .	4
3.2	Display math . . . . .	5
3.3	Associated Files . . . . .	5
3.4	Automatic mathml creation with luamml . . . . .	6
3.5	Options . . . . .	6
<b>4</b>	<b>Known current bugs, etc.</b>	<b>6</b>
4.1	Capture/grabbing problems . . . . .	7
4.2	Fake math . . . . .	7
4.3	Processor . . . . .	8
4.4	Other problems . . . . .	8
4.5	Other ToDos . . . . .	8

---

\*

<b>5</b>	<b>The Implementation</b>	<b>9</b>
5.1	File declaration . . . . .	9
5.2	Setup . . . . .	9
5.3	Data structures . . . . .	9
5.4	Tagging tools . . . . .	10
5.5	Code related to AF . . . . .	10
5.6	Mathstyle detection . . . . .	18
5.7	Tagging options . . . . .	19
5.8	Sockets . . . . .	19
5.8.1	Main inline math sockets . . . . .	19
5.8.2	Main display math sockets . . . . .	20
5.8.3	Internal sockets . . . . .	21
5.9	Interface commands . . . . .	26
5.10	Content grabbing . . . . .	27
5.11	Token-by-token inline grabbing . . . . .	29
5.12	Marking math environments . . . . .	31
5.13	Document commands . . . . .	35
5.14	\everymath and \everydisplay . . . . .	36
5.15	Modifying kernel environments . . . . .	37
5.16	Disable math grabbing in the begindocument hook . . . . .	38
5.17	Modifying amsmath . . . . .	38

## Index 44

# 1 Introduction

Todo: update all the documentation! Both here and (what little there is!) in the implementation section.

Tagging math involves a variety of tasks that require that math is captured before the typesetting

- When typesetting the math MC-tags and structure commands must be inserted at the begin and the end, and perhaps also around lines or other subparts of the equation.
- The source and/or a mathml-representation of the source must be available so that it can be (perhaps after some preprocessing) be used in an associated file or in an alternate text
- It must be possible to measure the math for e.g. a bbox setting.

This file implements capture of all math mode material at the outer level, i.e., a formula is captured in its entirety with inner text blocks (possibly containing further math) absorbed as part of the formula. For example,

```
\[ a \in A \text{ for all } a < 5 \]
```

would only result in a single capture of the tokens “`a\inA\forall a<5$`”.

## 2 Math capture

In the current setup

- \$, \(...\)` and \$\$ grab (through a command in \everymath/cseverydisplay) if the boolean \l\_@@\_collected\_bool is false. If the boolean is true they behave normally and can for example contain verbatim.
- All (registered) environments grab their body regardless of the state of the boolean. For `equation`, `equation*` and `math` this is a change as they no longer can contain verbatim.
- BUG: \[...] grabs if \l\_@@\_collected\_bool is false. If it is true it falls back to `equation*` and then errors because this can't find the end.

### 2.1 Code level interfaces

---

```
\math_register_env:n \math_register_env:n {\langle env\rangle}
\math_register_env:nn \math_register_env:nnn {\langle env\rangle} {\langle options\rangle}
```

---

Registers the `\langle env\rangle` as a math environment which should be captured and made available. This is necessary for all top-level math mode environments: low-level errors may result if these are not correctly set up. One or more key-value `\langle options\rangle` may also be given:

`arg-spec` The argument specification taken by the beginning of the environment; this is used to remove non-mathematical material.

---

```
\math_processor:n \math_processor:n {\langle tokens\rangle}
```

---

Declares that the captured math content should be passed to the `\langle tokens\rangle`, which will receive the environment type as #1 and the content as #2. The processing is done before the typesetting. It is not applied if `\ifmeasuring@` is true.

### 2.2 Document level interfaces

---

```
\RegisterMathEnvironment \RegisterMathEnvironment [{\langle options\rangle}] {\langle env\rangle}
```

---

Registers the `\langle env\rangle` as a math environment which should be captured and made available. This is necessary for all top-level math mode environments: low-level errors may result if these are not correctly set up. One or more key-value `\langle options\rangle` may also be given:

`arg-spec` The argument specification taken by the beginning of the environment; this is used to remove non-mathematical material.

## 3 Math tagging

The tagging code has to handle

- the embedding into the surrounding. This means
  - closing and reopening MC-chunks

- closing and reopening text/P-structures
- handling interferences of the tagging code with penalties and spacing.
- the actual tagging which means to do some or all of the following tasks:
  - setup content for an associated source file
  - setup content for an associated mathml file
  - setup content for the /Alt key
  - setup content for the /ActualText key
  - setup attributes
  - add associated files
  - add a Formula structure
  - surround subparts (e.g. lines) with Formula sub structures (perhaps with their own set of additional content)
  - surround elements of the equation with mathml structure elements (currently only luatex with luamml)

### 3.1 Inline math

The embedding code is added through the sockets

- `tagsupport/math/inline/begin`
- `tagsupport/math/inline/end`

The sockets simply push and pop the MC currently. Without tagging they use the noop-plug.

The actual tagging is done through the sockets

- `tagsupport/math/inline/formula/begin` This socket takes the math as argument and its code should output it for typesetting. Without tagging the socket uses the identity plug. The `default` plug of the socket calls these three internal sockets for the tagging support:
  - `tagsupport/math/content` This should set up the various content variables (empty variables are ignored by the structure code and so can be used to suppress a setting).
  - `tagsupport/math/struct/begin` This calls `\tag_struct_begin:n`. It should also write the associated files if needed.
  - `tagsupport/math/substruct/begin` this handles subparts. TODO: does it really make sense in inline math to have that??
- `tagsupport/math/inline/formula/end` This socket ends the formula structure(s). The `default` plug calls these internal sockets:
  - `tagsupport/math/substruct/end`
  - `tagsupport/math/struct/end`

## 3.2 Display math

*to be written*

## 3.3 Associated Files

The current code allows the attachment of two types of associated file to the Formula structure: the L<sup>A</sup>T<sub>E</sub>X source and a MathML representation. Technically both can be attached—AF is an array of file references—practically there can be problems with PDF consumers: e.g. ngpdf used both and so showed the equation twice (this has been corrected in the newest version) and Foxit seems to see only the first AF in the array (so we attach the mathml as first file).

The L<sup>A</sup>T<sub>E</sub>X source can be (and is) attached automatically. It can be suppressed by an option with `math/tex/AF=false`, see below.

The MathML is attached if the files `\jobname-mathml.html` and/or `\jobname-luamml-mathml.html` are found and if they contain a suitable MathML snippet for the current formula. If the files contain more than one suitable snippet (as identified by the hash) the first one is used. `\jobname-luamml-mathml.html` is automatically generated (see below section 3.4) and read after `\jobname-mathml.html`. This means that `\jobname-mathml.html` can contain improved versions of a formula.

The MathML processing can be suppressed globally by emptying the list of mathml files with `math/mathml/sources=`. Locally for a formula `math/mathml/AF=false` can be used.

For a MathML representation a file with such representations must be provided. If the equation is numbered the numbering should be part of the MathML as the `Lbl` sub-structure is ignored if an MathML is used (see [https://github.com/foxitsoftware/PDF\\_UA-2](https://github.com/foxitsoftware/PDF_UA-2)).

The MathML representation is given in a special format. It is meant to be a valid html file that can be viewed in a browser. For this it can start with `<!DOCTYPE html><html>` and end with `</html>` It should have the extension `.html`. The `<mathml>` content is read with special catcodes, so can contain ampersands, hashes, comment chars and unmatched braces such as `<mo>{</mo>`

The file should contain a number of representations in this format:

```
<div>
  <h2>\mml <key></h2>
  <p><source></p>
  <p><hash></p>
  <math <attributes> >
    <mathml>
      </math>
  </div>
```

The keywords `<div>`, `<h2>\mml`, `<p>`, `<math>`, `</math>` `</div>` are required as they are used to delimit the arguments by the L<sup>A</sup>T<sub>E</sub>X code.

`<key>` and `<source>` are only used for debugging, they help to identify the equation referred by this representation. The source should be used correctly escaped & and < so that if gives valid html!

`<attributes>` is not required either, but can e.g. contain attributes to improve the display in a browser:

```
<math alttext="\mathbf{G}" class="ltx_Math" display="inline">
```

It can also contain the name space declaration: `xmlns="http://www.w3.org/1998/Math/MathML"`  
<sup>1</sup>

By default the code tries at the begin of the document to read a file `\jobname-mathml.html` in the `html`-format. The file name can be changed with `mathml/setfiles={filename1,filename2}` (without extension, `html` is added automatically). If there is a list, all files are loaded. If a file doesn't exist it is ignored, only an info is written to the log.

Currently every MathML-snippet from a file is embedded into the PDF, it is not checked first if it is actually used (simply writing everything to the PDF is a bit easier than keeping everything in memory and also means that the snippets are one after the other in the PDF).

As mentioned above the MathML-AF can be suppressed for the equations in a group with `math/mathml/AF=false`, or completely by setting `math/mathml/sources=` in the preamble.

Files embedded in a PDF can be listed in the attachments panel of a PDF viewer. This is probably not so useful for lots of small files (but one could create collections), but as long as PDF editors or viewers don't offer proper support to access the AF it can help so have them there. The MathML are added by default, but the L<sup>A</sup>T<sub>E</sub>X source not. This can be changed with `viewer/pane/mathsource=true` (anywhere in the document) and `viewer/pane/mathml=false` (in the preamble, before the external file is read).

### 3.4 Automatic mathml creation with luamml

If lualatex is used, if the package `unicode-math` is used and if the package `luamml` is found then it will automatically generate the file `\jobname-luamml-mathml.html` with mathml representations of all math formulas. The generation of the file can be suppressed with `math/mathml/luamml=false`. If `unicode-math` is not used, the generation of the file can be forced with `math/mathml/luamml=true` or `math/mathml/luamml` but be aware that it is then probable that various symbols are mapped to the wrong unicode code points. The package is still quite experimental and the output should be checked. The `\jobname-luamml-mathml.html` file may be previewed in a browser although you may need to add additional css or javascript declarations to enable browser support for all mathml constructs. The file is then used in subsequent compilations and works also with pdflatex.

### 3.5 Options

## 4 Known current bugs, etc.

New Section, now with subsections.

As indicated, these lists are probably incomplete.

Some of these have been addressed in a more recent branch.

<sup>1</sup>But it is probably not needed and only blows up the PDF.

## 4.1 Capture/grabbing problems

1. Incorrect grabbing of \$-math when there is also explicit \$-math within a *text environment* that is itself within the math that should all be grabbed. For example,

```
$a\begin{minipage}{1cm}$b$\end{minipage}$
```

would only result in the capture of the tokens “`a\begin{minipage}{1cm}`”. This can be avoided by an additional brace group:

```
$a{\begin{minipage}{1cm}}$b$\end{minipage}}$
```

2. Similar incorrect grabbing with \$\$ also.
3. The grabbing, for all the display environments (and `\) \]`), needs to deal with nesting: `amsmath` contains code for this.
4. The math can't contain verbatim and verbatim-like commands. This is nothing new for the `amsmath` environments but changes \$ and `\[` and `equation*` (see e.g. tagging-project issue #30).
5. Begin and end of the math or math environment can not be hidden in commands. For example `>{$}1<{$}` in a tabular would lead to errors. Defining `\[` to fall back to `equation*` doesn't work if `equation*` is a grabbing environment.
6. The behaviour of `\[...]` is faulty. See above.

## 4.2 Fake math

In a number of places in L<sup>A</sup>T<sub>E</sub>X math commands (mainly \$) is used only for technical reason, e.g. to access a math font, to setup a symbol or to use `\vcenter`.

The code identifies such fake math mostly by making use of the `\m@th` command where two methods are used for the automatic detection:

- After grabbing math content the code checks if the content contains the token `\m@th` and if yes it doesn't call the processor before reinserting the content and perhaps adding tagging code. This method requires that the math can be grabbed (e.g. that the end dollar is visible) and that the `\m@th` is visible. It applies for example in `\@iiiparbox` where the code from `$\vcenter` to `\m@th$` is grabbed and put back. It does not work for example for `tabular` where the dollars and the `\m@th` token are spread around over three commands. `tabular` needs therefore manual intervention. A look in the list of usages (in `usage-of-m@th.md`) justifies this approach. All usages are either not math at all, or related to small elements that probably shouldn't be grabbed and processed on their own.
- `\m@th` is redefined so that it sets the boolean `\l_@@_collected_bool` to true. If `\m@th` is used inside math that has been grabbed this doesn't change much as the boolean is set by the grabbing anyway. For usages outside math the benefit is not so clear: The setting avoids that in L<sup>A</sup>T<sub>E</sub>X the epsilon is processed as math, but it also prevents that the content of the `amsmath` command `\boxed` is processed as math. It means that if one wants to reenable math processing inside some (fake) math one has to do it after `\m@th` calls.

Open problems

1. The grabbing code doesn't pass the info that it detected a `\m@th` token. This means that the tagging code has to do the same check (and doesn't do this in all cases yet).
2. Commands are missing to locally disable the grabbing and processing, e.g. to handle `tabular`.
3. It must be checked if setting the boolean in `\m@th` really makes sense or if commands like `\LaTeXe` should be handled manually.

### 4.3 Processor

The grabbed math is at first passed to the processor. The processor is not called in a measuring phase (from the amsmath `\ifmeasuring@`) and if the `\m@th` token is detected. It is not quite clear what purpose the processor has. As it is a public interface it can't be used for internal code. And typesetting happens later and the processor can't really change this. Currently it is mostly used for debugging and messages. If the `\m@th` is found the `\l_@fakemath_bool` is set, so if the code is changed this must be preserved.

### 4.4 Other problems

1. The presence of `\m@th` in association with `\ensuremath` does not necessarily indicate fakemath. This is because wanting `mathsurround` to be zero is very reasonable and common, *even when the math is genuine* (and hence needs to be collected).  
TODO: this claim needs some examples.
2. User-defined environments can create problems; but this area, of new, copied and changed environments, has not yet been developed.

Joseph wrote, inter alia:

My thinking [regarding] `\RegisterMathEnvironment`

- (New) Math environments should not be created-then-patched, but only generated by a [(future)] dedicated command (`\DeclareMathEnvironment`, presumably)
- Math environments created with `\tcmd` [commands] should not be copied, . . .
- Package authors should be able to manually set up math environments with a public boolean.

### 4.5 Other ToDos

1. Add (some of) the math display commands that were "lifted from plain", e.g., `\displaylines \eqalign(??)`.
2. The `breqn` package changes catcodes and that isn't yet covered by our mechanism.
3. `\intertext` is not correctly taken into account by the code splitting multiline math into subformulas.

`\MaybeStop` (temporarily) not executed, as it is unknown on Chris' system.

## 5 The Implementation

```
1 <@@=math>
2 <*kernel>
```

### 5.1 File declaration

Change description here?

```
3 \ProvidesFile{latex-lab-math.ltx}
4   [\ltlabmathdate\space
5   v\ltlabmathversion\space
6   Grab all the math(s) and tag it (experiments)]
7 Temp loading ...
8 \AddToHook{begindocument/before}{\RequirePackage{latex-lab-testphase-block}}
9 \ExplSyntaxOn
```

### 5.2 Setup

Loading `amsmath` is an absolute requirement: this avoids needing to have conditional definitions and deals with how to define `\[ / ]` neatly.

```
9 \AddToHook{begindocument/before}{ \RequirePackage { amsmath } }
```

### 5.3 Data structures

---

`\l__math_collected_bool` Tracks whether math mode material has been collected, which happens inside `amsmath` environments as well as those handled directly here. If true following math will not grab and/or process. See 2 for details.

```
10 \bool_new:N \l__math_collected_bool
```

---

`\l__math_fakemath_bool` Tracks whether math mode material has been identified as fake math during the grabbing phase, which happens currently if the grabbed contents contains the `\m@th` token.

Change first tl name below: ‘env’ => ‘info’?

```
11 \bool_new:N \l__math_fakemath_bool
```

Or do we need an extra

stop`\g_math_grabbed_env_tl`

`\g_math_grabbed_math_tl`

`\g__math_grabbed_env_tl` contains the name of the math environment (`math` in the case of inline math, `\g__math_grabbed_math_tl` the math content).

```
12 \tl_new:N \g__math_grabbed_env_tl
13 \tl_new:N \g__math_grabbed_math_tl
```

---

`\l__math_tmpa_tl` Temporary variables

`\l__math_tmpa_skip`

`\l__math_tmpa_str`

```
14 \tl_new:N \l__math_tmpa_tl
15 \skip_new:N \l__math_tmpa_skip
16 \str_new:N \l__math_tmpa_str
```

---

<pre>\l__math_content_alt_t1 \l__math_content_actual_t1 \l__math_content_AF_t1</pre>	Temporary variables to hold math content that should be used in actual or alt text and stored as AF.
--	--

---

```
17 \tl_new:N \l__math_content_alt_t1
18 \tl_new:N \l__math_content_actual_t1
19 \tl_new:N \l__math_content_AF_source_t1
20 \tl_new:N \l__math_content_AF_source_tmpa_t1
21 \tl_new:N \l__math_content_AF_mathml_t1
```

## 5.4 Tagging tools

The following commands implement small tagging code chunks. This should probably be collected and moved into tagpdf later.

- `\__tag_tool_close_P:` This closes a P/text-chunk, both the MC and the structure and increases the counter manually.

```
22 \cs_new_protected:Npn \__tag_tool_close_P:
23 {
24     \tag_if_active:T
25     {
26         \tag_mc_end: %end P-chunk, should perhaps be \tag_mc_end_push: ...
27         \__tag_gincr_para_end_int:
28         \__tag_check_para_end_show:nn{red}{} %debug: show para
29         \tag_struct_end:
30     }
31 }
```

(End of definition for `\__tag_tool_close_P:..`)

We add also an attribute.

```
32 \tl_new:N\l__math_attribute_class_t1
33 \tagpdfsetup
34     {role/new-attribute = {inline}    {/0 /Layout /Placement/Inline},
35      role/new-attribute = {display}   {/0 /Layout /Placement/Block},
36 }
```

## 5.5 Code related to AF

Booleans to handle the options.

---

```
\l__tag_math_texsource_AF_bool
\l__tag_math_texsource_pane_bool
\l__tag_math_mathml_AF_bool
\g__tag_math_mathml_AF_bool
\l__tag_math_mathml_pane_bool
\l__tag_math_alt_bool
\g__tag_math_luamml_t1
```

---

The variable `\g__tag_math_luamml_t1` is initially 0 and the user key can set it to -1 or 1. This allows to distinguish the unset case from a value set by the user.

```
37 \bool_new:N\l__tag_math_texsource_AF_bool
38 \bool_new:N\l__tag_math_texsource_pane_bool
39 \bool_new:N\l__tag_math_mathml_AF_bool
40 \bool_new:N\g__tag_math_mathml_AF_bool
41 \bool_new:N\l__tag_math_mathml_pane_bool
42 \bool_new:N\l__tag_math_alt_bool
43 \tl_new:N\g__tag_math_luamml_t1
44 \tl_gset:Nn\g__tag_math_luamml_t1 {0}
```

---

```
\g__math_mathml_total_int
\g__math_mathml_int
\g__math_math_total_int
\g__math_mathml_AF_found_int
\g__math_mathml_AF_attached_int
```

---

`\g__math_mml_total_int` records the mathml fragments read in. `\g__math_mml_int` records the mathml fragments read in with a different hash. `\g__math_AF_total_int` records the number of math structures that try to attach a mathml AF. `\g__math_AF_found_int` records the number of math structures for which a fitting mathml is found. `\g__math_AF_attached_int` records the number of math structures which got a mathml fragment (if mathml-AF are not disabled locally this should be the equal to the previous number).

```
45 \int_new:N\g__math_mathml_total_int
46 \int_new:N\g__math_mathml_int
47 \int_new:N\g__math_math_total_int
48 \int_new:N\g__math_mathml_AF_found_int
49 \int_new:N\g__math_mathml_AF_attached_int
```

---

```
\l__tag_math_mathml_files_clist
```

---

A sequence to store the file list for the mathml. If luatex is detected with also check the luamml file.

```
50 \clist_new:N\l__tag_math_mathml_files_clist
51 \clist_put_right:Ne\l__tag_math_mathml_files_clist
52   {\c_sys_jobname_str-mathml,\c_sys_jobname_str-luamml-mathml}
```

This is the internal variant of the `\mml` command.

```
\__math_AF_mml:nnnn
53 \cs_new_protected:Npn \__math_AF_mml:nnnn #1 #2 #3 #4
54 %#1 number, #2 tex source for debugging, #3 hash, #4 mathml
55 {
56   \int_gincr:N \g__math_mathml_total_int
```

mathml with the same hash should be included only once:

```

57      \tl_if_exist:cF { g__math_mathml_#3_tl }
58      {
59          \int_gincr:N \g__math_mathml_int

```

a simple Desc key, take care that it is a valid string!

```

60      \pdfdict_put:nne {l_pdffile/Filespec} {Desc}{(mathml-#1)}
61      \pdffile_embed_stream:nnN {#4}{mathml-#1.xml}\l__math_tmpa_tl

```

not strictly necessary but makes the files visible in the file attachment page

```

62      \bool_if:NT \l__tag_math_mathml_pane_bool
63          {\pdfmanagement_add:nne {Catalog/Names}{EmbeddedFiles}{\l__math_tmpa_tl}}
64          \tl_new:c{g__math_mathml_#3_tl}
65          \tl_gset_eq:cN{g__math_mathml_#3_tl}\l__math_tmpa_tl
66      }
67  }

```

(End of definition for  $\_\_math\_AF\_mml:nnnn$ .)

The html reader.

```

68 \cs_new_protected:Npn \_\_math_AF_html_reader:w#1</h2>#2<p>#3</p>#4<p>#5</p>#6<math{
69     \begingroup
70         \char_set_catcode_other:N\{
71         \char_set_catcode_other:N\
72         \char_set_catcode_other:N\#
73         \char_set_catcode_other:N\%
74         \_\_math_AF_html_reader_verb:w{#1}{#3}{#5}<math
75     }
76 \cs_new_protected:Npn \_\_math_AF_html_reader_verb:w#1#2#3#4~</div>{
77     \endgroup
78     \_\_math_AF_mml:nnnn{#1}{#2}{#3}{#4}
79 }

```

As with luatex we write two files we define a few constants for the shared texts.

```

\c__math_mathml_write_init_tl
\l__math_mathml_write_before_tl
\c__math_mathml_write_after_tl
\c__math_mathml_write_final_tl
80 \tl_const:Nn \c__math_mathml_write_init_tl
81  {
82      <!DOCTYPE~html>
83      \iow_newline:
84      <html>
85      \iow_newline:
86  }
87 \tl_new:N \l__math_mathml_write_before_tl
88 \tl_const:Nn \c__math_mathml_write_after_tl
89  {
90      \iow_newline:
91      </div>
92      \iow_newline:
93  }
94 \tl_const:Nn \c__math_mathml_write_final_tl
95  {
96      </html>
97  }

```

(End of definition for  $\c__math_mathml_write_init_tl$  and others.)

`h/mathml/write/prepare (socket)` To prepare the hash and the starting command we use a socket, so that both the dummy and luamml can make use of it.

```

98 \socket_new:nn {tagsupport/math/mathml/write/prepare}{0}

On (plug)
99 \socket_new_plug:nnn{tagsupport/math/mathml/write/prepare}{On}
100 {
101   \str_set:NV\l__math_tmpa_str\l__math_content_AF_source_tl
102   \str_replace_all:Nnn\l__math_tmpa_str{&}{&amp;}
103   \str_replace_all:Nnn\l__math_tmpa_str{<}{&lt;}
104   \tl_set:Nn \l__math_mathml_write_before_tl
105   {
106     <div>
107     \iow_newline:
108     <h2>\c_backsplash_str mml\c_space_tl \int_use:N \g__math_math_total_int </h2>
109     \iow_newline:
110     <p>\l__math_tmpa_str</p>
111     \iow_newline:
112     <p>\l__math_content_hash_tl </p>
113     \iow_newline:
114   }
115 }
```

With luatex we automatically generate mathml with luamml if the package can be loaded and unicode-math is detected. We start the process in the begindocument/end hook so that the reading from a previous compilation can happen before!

```

116 \sys_if_engine_luatex:T
117 {
118   \file_if_exist:nT { luamml.sty }
119   {
120     \RequirePackage { luamml }
Temporary (!) fixes for endarray
121   \AddToHook{package/array/after}
122   {
123     \cs_set:Npn \endarray
124     {
125       \tbl_crcr:n{endarray}
126       \__luamml_array_save_array:
127       \egroup
128       \UseTaggingSocket{tbl/finalize}
129       \tbl_restore_outer_cell_data:
130       \egroup
131       \mode_if_math:T { \__luamml_array_finalize_array: }
132       \arrayright
133       \gdef \arrayreamble {}
134     }
135     \cs_set:Npn \@classz
136     {
137       \@classx
138       \tempcnta \count@
139       \prepnxt@tok
140       \addtopreamble {
141         \ifcase \chnum
```

```

142   \hfil
143   \hskip 1sp
144   \d@llarbegin
145   \cs_if_eq:NNTF \d@llarbegin \begingroup {
146     \insert@column
147     \d@llarend
148   } {
149     \__luamml_array_init_col:
150     \insert@column
151     \luamml_flag_save:nn {} {mtd}
152     \d@llarend
153     \__luamml_array_finalize_col:w 0~
154   }
155   \do@row@strut
156   \hfil
157 \or
158   \hskip 1sp
159   \d@llarbegin
160   \cs_if_eq:NNTF \d@llarbegin \begingroup {
161     \insert@column
162     \d@llarend
163   } {
164     \__luamml_array_init_col:
165     \insert@column
166     \luamml_flag_save:nn {} {mtd}
167     \d@llarend
168     \__luamml_array_finalize_col:w 1~
169   }
170   \do@row@strut
171   \hfil
172 \or
173   \hfil
174   \hskip 1sp
175   \d@llarbegin
176   \cs_if_eq:NNTF \d@llarbegin \begingroup {
177     \insert@column
178     \d@llarend
179   } {
180     \__luamml_array_init_col:
181     \insert@column
182     \luamml_flag_save:nn {} {mtd}
183     \d@llarend
184     \__luamml_array_finalize_col:w 2~
185   }
186   \do@row@strut
187 \or
188   \setbox \ar@mcellbox \vbox \c@startpbox { \c@nextchar }
189   \insert@pcolumn
190   \c@endpbox
191   \ar@align@mcell
192   \do@row@strut
193 \or
194   \vtop \c@startpbox { \c@nextchar }
195   \insert@pcolumn

```

```

196          \endpbox
197          \do@row@strut
198      \or
199          \vbox \startpbox { \nextchar }
200              \insert@pcolumn
201          \endpbox
202          \do@row@strut
203      \fi
204  }
205  \prepnext@tok
206 }
207 }

208 \AddToHook{begindocument/end}
209 {
210     \str_case:on \g_tag_math_luamml_tl
211     {
212         { 1 } {
213             \__math_luamml_activate_write:
214             \msg_note:nnnn { tag }
215                 { luamml-status }{ enabled }{ create }
216         }
217         {-1 } {
218             \msg_note:nnnn { tag }
219                 { luamml-status }{ disabled }{ not-create }
220         }
221         { 0 }
222         {
223             \ifpackageloaded { unicode-math }
224             {
225                 \__math_luamml_activate_write:
226                 \msg_note:nnnn { tag }
227                     { luamml-status }{ enabled }{ create }
228             }
229             \msg_warning:nn { tag }{ unicode-math-missing } }
230         }
231     }
232 }
233 }

234 \msg_new:nnn { tag }{ luamml-status }
235 {
236     luamml~has~been~#1~and~will~#2~an~MathML~file.
237 }

238 }

239 \msg_new:nnn { tag }{ unicode-math-missing }
240 {
241     The-package~unicode-math~is~missing\\
242     luamml~will~not~create~an~MathML~file.\\
243     To~avoid~this~warning~load~unicode-math~\\
244     or~disable~luamml~with~\\
245     \tl_to_str:n{\tagpdfsetup{math/mathml/luamml=false}}\\
246     or~force~luamml~with~\\
247     \tl_to_str:n{\tagpdfsetup{math/mathml/luamml=true}}
248 }

249 }

```

```

250 \cs_new_protected:Npn \__math_luamml_activate_write:
251 {
to avoid that nothing is written in the first run, we must activate the sockets:
252 \bool_gset_true:N\g__tag_math_mathml_AF_bool
253 \AssignSocketPlug{tagsupport/math/struct/begin}{test-mathml}
254 \AssignSocketPlug{tagsupport/math/struct/end}{test-mathml}
255 \AssignSocketPlug{tagsupport/math/substruct/begin}{single}
256 \AssignSocketPlug{tagsupport/math/substruct/end}{single}
257 \int_set:Nn \l__luamml_pretty_int { 5 }
258 \RegisterFamilyMapping{symsymbols}{oms}
259 \RegisterFamilyMapping{symletters}{oml}
260 \AssignSocketPlug{tagsupport/math/mathml/write/prepare}{On}
261 \iow_new:N \g__math_luamml_iow
262 \iow_open:Nn \g__math_luamml_iow {\c_sys_jobname_str-luamml-mathml.html}
263 \iow_now:Ne \g__math_luamml_iow { \c__math_mathml_write_init_tl }
264 \cs_new:Npn \__math_luamml_output_hook:n ##1
265 {
266     \tl_if_empty:NF \l__math_mathml_write_before_tl
267     {
268         \iow_now:Ne \g__math_luamml_iow
269         {
270             \l__math_mathml_write_before_tl
271             ##1
272             \c__math_mathml_write_after_tl
273         }
274     }
275 }
276 \__luamml_register_output_hook:N \__math_luamml_output_hook:n

```

this starts the process and set flag to 3, not really needed, as it is the default but set here for clarity:

```
277 \luamml_flag_process:
```

At the end of the document we must finish and close the file:

```

278 \AddToHook{enddocument/afterlastpage}
279 {
280     \iow_now:Ne \g__math_luamml_iow
281     { \c__math_mathml_write_final_tl }
282     \iow_close:N \g__math_luamml_iow
283 }
284 }
```

And now a key to deactivate luamml

```

285 \keys_define:nn { __tag / setup }
286 {
287     math/mathml/luamml .choice: ,
288     math/mathml/luamml/true .code:n = {\tl_gset:Nn \g__tag_math_luamml_tl{1}},
289     math/mathml/luamml/false .code:n = {\tl_gset:Nn \g__tag_math_luamml_tl{-1}},
290     math/mathml/luamml .default:n = true,
291     math/mathml/luamml .usage:n=preamble
292 }
```

`port/math/mathml/write (socket)` This writes a html-dummy with the hash and the math content. This should be optional, so it uses a socket that can be disabled

```

294 \socket_new:nn {tagsupport/math/mathml/write}{0}

On (plug)

295 \socket_new_plug:nnn{tagsupport/math/mathml/write}{On}
296 {
297   \iow_now:Ne \g__math_writedummy_iow
298   {
299     \l__math_mathml_write_before_tl
300     <math></math>
301     \c__math_mathml_write_after_tl
302   }
303 }
```

And now a key to activate the socket.

```

304
305 \keys_define:nn { __tag / setup }
306 {
307   math/mathml/write-dummy .code:n =
308   {
309     \bool_gset_true:N \g__tag_math_mathml_AF_bool
310     \tl_if_exist:NF\g__math_writedummy_iow
311     {
312       \iow_new:N \g__math_writedummy_iow
313       \iow_open:Nn \g__math_writedummy_iow
314       {
315         \c_sys_jobname_str-mathml-dummy.html
316       }
317       \iow_now:Ne \g__math_writedummy_iow
318       {
319         \c__math_mathml_write_init_tl
320       }
321     \AssignSocketPlug {tagsupport/math/mathml/write/prepare}{On}
322     \AssignSocketPlug {tagsupport/math/mathml/write}{On}
323     \AddToHook{enddocument/afterlastpage}
324     {
325       \iow_now:Ne \g__math_writedummy_iow
326       {
327         \c__math_mathml_write_final_tl
328       }
329     }
330   },
331   math/mathml/write-dummy .usage:n=preamble
332 }

\__math_AF_process_mathml_files:
333 \box_new:N\l__math_tmpa_box
334 \cs_new_protected:Npn \__math_AF_process_mathml_files:
335 {
336   \hbox_set:Nn \l__math_tmpa_box
337   {
338     \pdfdict_put:nnn { l_pdffile/Filespec }{AFRelationship} { /Supplement }
```

```

339     \pdfdict_put:nne
340         { l_pdffile }{Subtype}
341         { \pdf_name_from_unicode_e:n{application/mathml+xml} }
342     \char_set_catcode_other:N \#
343     \cs_set_eq:NN\mml \__math_AF_html_reader:w
344     \clist_map_inline:Nn \l__tag_math_mathml_files_clist
345         {
346             \file_if_exist:nTF {##1.html}
347                 {
348                     \typeout{Info:~reading~mathml~file-##1}
349                     \file_input:n {##1.html}
350                     \bool_gset_true:N\g__tag_math_mathml_AF_bool
351                 }
352                 {
353                     \typeout{Info:~mathml~file~##1~does~not~exist}%info message
354                 }
355             }
356         }
357     \bool_if:NT\g__tag_math_mathml_AF_bool
358         {
359             \typeout{Info:~Activating~mathml~support}
360             \AssignSocketPlug{tagsupport/math/struct/begin}{test-mathml}
361             \AssignSocketPlug{tagsupport/math/struct/end}{test-mathml}

```

mathml handling doesn't like subparts, so we disable them for now:

```

362         \AssignSocketPlug{tagsupport/math/substruct/begin}{single}
363         \AssignSocketPlug{tagsupport/math/substruct/end}{single}
364         \AddToHook{enddocument/info}
365             {
366                 \iow_term:n{MathML~statistic}
367                 \iow_term:n{=====}
368                 \iow_term:e{==>-\int_use:N\g__math_mathml_total_int\c_space_tl
369                 MathML~fragments~read}
370                 \iow_term:e{==>-\int_use:N\g__math_mathml_int\c_space_tl
371                 different~MathML~fragments}
372                 \iow_term:e{==>-\int_use:N\g__math_mathml_total_int\c_space_tl
373                 math~fragments~found}
374                 \iow_term:e{==>-\int_use:N\g__math_mathml_AF_found_int\c_space_tl
375                 fitting~MathML~AF~found}
376                 \iow_term:e{==>-\int_use:N\g__math_mathml_AF_attached_int\c_space_tl
377                 MathML~AF~attached}
378             }
379         }
380     }
381     \AddToHook{begindocument}{\__math_AF_process_mathml_files:}

```

(End of definition for `\__math_AF_process_mathml_files:.`)

## 5.6 Mathstyle detection

In some cases we need to detect the mathstyle used in a `\mathchoice` command and to disable/enable tagging in the unused branches. This is currently only used in the amstext command `\text` but is perhaps also needed in other cases, so we create a general command.

```

\l__math_mathstyle_int
\g__math_mathchoice_int
  mathstyle
 382 \int_new:N \l__math_mathstyle_int
 383 \int_new:N \g__math_mathchoice_int
 384 \property_new:nnnn{mathstyle}{now}{-1}{\int_use:N \l__math_mathstyle_int }

(End of definition for \l__math_mathstyle_int, \g__math_mathchoice_int, and mathstyle. This function is documented on page ??.)

```

For now internal, but perhaps will need a public version. The command should be used in every branch of a `\mathchoice` (with the correct mathstyle number) and with an unique label (which should be the same in every branch). `\g__math_mathchoice_int` can be e.g. increased before the `\mathchoice` and then used.

```

\__math_tag_if_mathstyle:nn
 385 \cs_new_protected:Npn \__math_tag_if_mathstyle:nn #1 #2
 386   %#1 refers to label
 387   %#2 is a number for the mathstyle (typically 0,2,4,6)
 388   {
 389     \int_set:Nn \l__math_mathstyle_int {#2}
 390     \property_record:nn {#1} {mathstyle}
 391     \int_compare:nNnTF { \property_ref:nn {#1}{mathstyle} } = { #2 }
 392       { \tag_start: }{ \tag_stop: }
 393   }
 394 \cs_generate_variant:Nn \__math_tag_if_mathstyle:nn {en}

(End of definition for \__math_tag_if_mathstyle:nn.)

```

## 5.7 Tagging options

```

395 \keys_define:nn { __tag / setup }
396   {
397     math/mathml/sources .clist_set:N = \l__tag_math_mathml_files_clist,
398     math/alt/use .bool_set:N = \l__tag_math_alt_bool,
399     viewer/pane/mathml .bool_set:N = \l__tag_math_mathml_pane_bool,
400     viewer/pane/mathml .initial:n = true,
401     viewer/pane/mathsource .bool_set:N = \l__tag_math_texsource_pane_bool,
402     math/mathml/AF .bool_set:N = \l__tag_math_mathml_AF_bool,
403     math/mathml/AF .initial:n = true,
404     math/tex/AF .bool_set:N = \l__tag_math_texsource_AF_bool,
405     math/tex/AF .initial:n = true
406   }

```

## 5.8 Sockets

### 5.8.1 Main inline math sockets

`port/math/inline/begin (socket)` The first two sockets are meant to embed inline math into the surrounding (so to support `math/inline/end (socket)`) close/reopen e.g. MC-chunks). The other two implement the actual formula structure.  
`h/inline/formula/begin (socket)` The formula sockets are despite their naming not symmetric: the begin socket is issued after the math has started, while the end socket is after the math!

```

407 \socket_new:nn {tagsupport/math/inline/begin}{0}
408 \socket_new:nn {tagsupport/math/inline/end}{0}
409 \socket_new:nn {tagsupport/math/inline/formula/begin}{1} %
410 \socket_new:nn {tagsupport/math/inline/formula/end}{0}

```

```

MC (plug)
 411 \socket_new_plug:nnn
 412   {tagsupport/math/inline/begin}
 413   {MC}
 414   {\tag_mc_end_push:}
 415 \socket_new_plug:nnn
 416   {tagsupport/math/inline/end}
 417   {MC}
 418   {\tag_mc_begin_pop:n{}}

```

We probably will want to test different tagging recipes.

```

default (plug)
 419 \socket_new_plug:nnn
 420   {tagsupport/math/inline/formula/begin}
 421   {default}
 422   {
 423     \socket_use:n{tagsupport/math/content}
 424     \socket_use:n{tagsupport/math/struct/begin}
TODO: does inline math need subformula handling?
 425     % inner formula if multiple parts (not really implemented yet)
 426     \socket_use:n{tagsupport/math/substruct/begin}
 427     #1
 428     \socket_use:n{tagsupport/math/end}
 429   }
 430 \socket_new_plug:nnn
 431   {tagsupport/math/inline/formula/end}
 432   {default}
 433   {
 434     \socket_use:n{tagsupport/math/substruct/end}
 435     \socket_use:n{tagsupport/math/struct/end}
 436   }

```

### 5.8.2 Main display math sockets

`port/math/display/begin (socket)` The first two sockets are meant to embed display math into the surrounding (so to `port/math/display/end (socket)`) close/reopen e.g. MC-chunks and P-structure). The other two implement the actual `/display/formula/begin (socket)` formula structure. The formula sockets are despite their naming not symmetric: the `math/display/formula/end (socket)` begin socket is issued after the math has started, while the end socket is after the math!

```

 437 \socket_new:nn {tagsupport/math/display/begin}{0}
 438 \socket_new:nn {tagsupport/math/display/end}{0}
 439 \socket_new:nn {tagsupport/math/display/formula/begin}{1} %
 440 \socket_new:nn {tagsupport/math/display/formula/end}{0}

default (plug)
 441 \socket_new_plug:nnn
 442   {tagsupport/math/display/begin}
 443   {default}
 444   { \__tag_tool_close_P:  }
 445 \socket_new_plug:nnn
 446   {tagsupport/math/display/end}
 447   {default}
 448   {

```

```

449     }
450 
default (plug)
451   \socket_new_plug:nnn
452   {tagsupport/math/display/formula/begin}
453   {default}
454   {
455     \socket_use:n{tagsupport/math/content}
456     \socket_use:n{tagsupport/math/struct	begin}
457     \socket_use:n{tagsupport/math/substruct	begin}
458     #1
459     \socket_use:n{tagsupport/math/end}
460   }
461   \socket_new_plug:nnn
462   {tagsupport/math/display/formula/end}
463   {default}
464   {
465     \socket_use:n{tagsupport/math/substruct	end}
466     \socket_use:n{tagsupport/math/struct	end}
467   }

```

### 5.8.3 Internal sockets

---

#### \l\_\_math\_content\_template\_tl

---

The default text used as alt or actual text.

```

467 \tl_new:N\l__math_content_template_tl
468 \tl_set:Nn \l__math_content_template_tl
469   {
470     LaTeX~ formula~ starts~
471     \exp_not:N\begin{\g__math_grabbed_env_tl}
472     \c_space_tl
473     \exp_not:V\g__math_grabbed_math_tl
474     \c_space_tl
475     \exp_not:N\end{\g__math_grabbed_env_tl}
476     \c_space_tl LaTeX~ formula~ ends~
477   }

```

---

**\l\_\_math\_texsource\_template\_tl**

The default text used as texsource

```
478 \tl_new:N\l__math_texsource_template_tl
479 \tl_const:Nn\c__math_inline_env_tl {math}
480 \tl_set:Nn \l__math_texsource_template_tl
481 {
482     \tl_if_eq:NNTF\g__math_grabbed_env_tl\c__math_inline_env_tl
483     {
484         $
485         \exp_not:V\g__math_grabbed_math_tl
486         $
487     }
488     {
489         \exp_not:N\begin{\g__math_grabbed_env_tl}
490         \exp_not:V\g__math_grabbed_math_tl
491         \exp_not:N\end{\g__math_grabbed_env_tl}
492     }
493 }
```

`tagsupport/math/content (socket)` The math content is stored in associated files and used for actual and alternative text. As the exact text is still unclear we use a socket to be able to test variants. The socket should set all four tl vars above, if needed to identical values. It can use the two variables `\g__math_grabbed_env_tl` and `\g__math_grabbed_math_tl`

```
494 \socket_new:nn {tagsupport/math/content}{0}
```

Some default sockets to set the contents. TODO: think about naming convention. TODO: think how this should organized so that one has options to change from the outside and so that there are less repetitions.

**actual+source (plug)**

```
495 \socket_new_plug:nnn
496   {tagsupport/math/content}
497   {actual+source}
498   {
499     \tl_set:Ne\l__math_content_actual_tl
500     {
501         \l__math_content_template_tl
502     }
503     \tl_set:Ne \l__math_content_AF_source_tl
504     {
505         \l__math_texsource_template_tl
506     }
507     \tl_set:Nn    \l__math_content_AF_mathml_tl {}
508     \tl_set:Nn    \l__math_content_alt_tl  {}
509 }
```

**alt+source (plug)**

```
510 \socket_new_plug:nnn
511   {tagsupport/math/content}
512   {alt+source}
513   {
514     \tl_set:Ne\l__math_content_alt_tl
```

```

515     {
516         \l_math_content_template_t1
517     }
518 \tl_set:Ne \l_math_content_AF_source_t1
519     {
520         \l_math_texsource_template_t1
521     }
522 \tl_set:Nn    \l_math_content_AF_mathml_t1 {}
523 \tl_set:Nn    \l_math_content_actual_t1   {}
524 }

525 \socket_assign_plugin:nn {tagsupport/math/content}{alt+source}

```

`port/math/struct/begin (socket)` For the main structure we use a socket too. This allow e.g. to create a special one  
`support/math/struct/end (socket)` for luamml which setups additional objects. The begin socket can use the two variables  
`\g_math_grabbed_env_t1` and `\g_math_grabbed_math_t1`

```

526 \socket_new:nn {tagsupport/math/struct/begin}{0}
527 \socket_new:nn {tagsupport/math/struct/end}{0}

```

`default (plug)` TODO: think about some naming convention ...

```

528 \socket_new_plugin:nnn
529   {tagsupport/math/struct/begin}
530   {default}
531   {
532     \bool_if:NTF\l_tag_math_texsource_AF_bool
533     { \tl_set_eq:NN \l_math_content_AF_source_tmpa_t1 \l_math_content_AF_source_t1 }
534     { \tl_clear:N \l_math_content_AF_source_tmpa_t1 }
535   \tag_struct_begin:n
536   {
537     tag=Formula,
538     texsource  = \l_math_content_AF_source_tmpa_t1,
539     title-o   = \g_math_grabbed_env_t1,
540     actualtext = \l_math_content_actual_t1,
541     alt       = \l_math_content_alt_t1
542   }
543 }
544 \socket_new_plugin:nnn
545   {tagsupport/math/struct/end}
546   {default}
547   { \tag_struct_end: }

548
549 \socket_assign_plugin:nn {tagsupport/math/struct/begin}{default}
550 \socket_assign_plugin:nn {tagsupport/math/struct/end}{default}

```

`test-mathml (plug)` This (test-)socket tries to add a mathml-AF to formula. It is activated if a mathml.html has been found and loaded. Additionally it also sets an attribute (this can perhaps be done by default anyway.) As it disturbs the reading of the AF it currently deactivates the /Alt key, unless it has been reenabled with `math/alt/use=true`

```

551 \cs_generate_variant:Nn \str_mdfive_hash:n {o}
552 \tl_new:N\l_math_content_hash_t1

```

we need to save the grabbed math:

```

553 \tl_new:N\l_math_grabbed_math_t1

```

the socket definition

```

554 \socket_new_plug:nmn
555 {tagsupport/math/struct/begin}
556 {test-mathml}
557 {
558   \int_gincr:N\g__math_math_total_int
559   \tl_set:Ne\l__math_content_hash_tl
560   {\str_mdfive_hash:o { \l__math_content_AF_source_tl }}
561   \tl_set_eq:NN\l__math_grabbed_math_tl\g__math_grabbed_math_tl
562   \tl_if_eq:NnTF\g__math_grabbed_env_tl {math}
563   {
564     \tl_set:Nn\l__math_attribute_class_tl{inline}
565   }
566   {
567     \tl_set:Nn\l__math_attribute_class_tl{display}
568   }
569   \bool_if:NF\l__tag_math_alt_bool
570   { \tl_set:Nn \l__math_content_alt_tl{} }

```

debugging option. TODO: hide in debug key.

```

571 \tl_if_exist:cTF { g__math_mathml_ \l__math_content_hash_tl _tl }
572 {
573   \int_gincr:N\g__math_mathml_AF_found_int
574   \bool_if:NTF \l__tag_math_mathml_AF_bool
575   {
576     \int_gincr:N\g__math_mathml_AF_attached_int
577     \typeout {Inserting~mathml~with~Hash~\l__math_content_hash_tl}
578   }
579   {
580     \typeout {Ignoring~mathml~with~Hash~\l__math_content_hash_tl}
581   }
582 }
583 {
584   \typeout{WARNING:~mathml~missing~for~hash~\l__math_content_hash_tl}
585 }
586 \socket_use:n {tagsupport/math/mathml/write/prepare}
587 \socket_use:n {tagsupport/math/mathml/write} % write hash if request
588 \bool_if:NTF\l__tag_math_texsource_AF_bool
589 { \tl_set_eq:NN \l__math_content_AF_source_tmpa_tl \l__math_content_AF_source_tl }
590 { \tl_clear:N \l__math_content_AF_source_tmpa_tl }
591 \tag_struct_begin:n
592 {
593   tag=Formula,
594   attribute-class=\l__math_attribute_class_tl, %
595   AFref      =
596   \bool_if:NT\l__tag_math_mathml_AF_bool
597   {
598     \cs_if_exist_use:c {g__math_mathml_ \l__math_content_hash_tl _tl}
599   },
600   texsource    = \l__math_content_AF_source_tmpa_tl, % should be after mathml AF!
601   title-o     = \g__math_grabbed_env_tl,      %
602   alt         = \l__math_content_alt_tl
603 }
604 }
```

not really needed but looks more symmetric:

```
605 \socket_new_plug:nnn
606 {tagsupport/math/struct/end}
607 {test-mathml}
608 {
609     \tag_struct_end:
610 }
```

t/math/substruct/begin (*socket*) This holds the code to handle subparts of the formula.

port/math/substruct/end (*socket*)  
611 \socket\_new:nn {tagsupport/math/substruct/begin}{0}
612 \socket\_new:nn {tagsupport/math/substruct/end}{0}

default (*plug*)

```
613 \socket_new_plug:nnn
614 {tagsupport/math/substruct/begin}
615 {default}
616 { \grabaformulapartandstart }
617 \socket_new_plug:nnn
618 {tagsupport/math/substruct/end}
619 {default}
620 {
621     \tagmcend
622     \if@subformulas
623         \tagstructend
624     \fi
625 }
626 \socket_assign_plug:nn {tagsupport/math/substruct/begin}{default}
627 \socket_assign_plug:nn {tagsupport/math/substruct/end}{default}
```

single (*plug*) We need an option to disable subparts as it is unclear if consumers can handle them:

```
628 \socket_new_plug:nnn
629 {tagsupport/math/substruct/begin}
630 {single}
631 {
632     \typeout{====>subpart~splitting~deactivated}
633     \typeout{====>grabbed~math=\meaning\g_math_grabbed_math_tl}
634     \tag_mc_begin:nn
635 }
636 \socket_new_plug:nnn
637 {tagsupport/math/substruct/end}
638 {single}
639 { \tag_mc_end: }
```

tagsupport/math/end (*socket*) A socket used at the end of the math (before the closing dollar(s)) which can e.g. set a flag for luamml.

```
640 \socket_new:nn {tagsupport/math/end}{0}
```

\\_\\_tag\\_math\\_disable: Similar to the table code we collect the plugs that should be assigned to do nothing if we don't want tagging

```
641 \cs_new_protected:Npn \_\_tag\_math\_disable:
642 {
643     \socket_assign_plug:nn {tagsupport/math/inline/begin}{noop}
644     \socket_assign_plug:nn {tagsupport/math/inline/end}{noop}
```

```

645   \socket_assign_plug:nn {tagsupport/math/inline/formula/begin}{identity}
646   \socket_assign_plug:nn {tagsupport/math/inline/formula/end}{noop}
647   \socket_assign_plug:nn {tagsupport/math/display/begin}{noop}
648   \socket_assign_plug:nn {tagsupport/math/display/end}{noop}
649   \socket_assign_plug:nn {tagsupport/math/display/formula/begin}{identity}
650   \socket_assign_plug:nn {tagsupport/math/display/formula/end}{noop}
651 }

```

(End of definition for `\_\_tag\_math\_disable::`)

`\_\_tag\_math\_enable:` Similar to the table code we collect the default plugs that should be assigned if we want tagging

```

652 \cs_new_protected:Npn \_\_tag_math_enable:
653 {
654   \socket_assign_plug:nn {tagsupport/math/inline/begin}{MC}
655   \socket_assign_plug:nn {tagsupport/math/inline/end}{MC}
656   \socket_assign_plug:nn {tagsupport/math/inline/formula/begin}{default}
657   \socket_assign_plug:nn {tagsupport/math/inline/formula/end}{default}
658   \socket_assign_plug:nn {tagsupport/math/display/begin}{default}
659   \socket_assign_plug:nn {tagsupport/math/display/end}{default}
660   \socket_assign_plug:nn {tagsupport/math/display/formula/begin}{default}
661   \socket_assign_plug:nn {tagsupport/math/display/formula/end}{default}
662 }

```

(End of definition for `\_\_tag\_math\_enable::`)

At begin document we can activate:

```
663 \AtBeginDocument{\tag_if_active:T{\_\_tag_math_enable: }}
```

## 5.9 Interface commands

`\_\_math_process:nn`  
`\_\_math_process:Vn`

```

664 \cs_new_protected:Npn \_\_math_process:nn #1#2
665 {
666   \legacy_if:nF { measuring@ }
667   {
668     \tl_if_in:nnTF {#2} { \m@th }
669     { \bool_set_true:N\l__math_fakemath_bool }
670     { \tl_trim_spaces_apply:nN {#2} \_\_math_process_auxi:nn {#1} }
671   }
672 }
673 \cs_generate_variant:Nn \_\_math_process:nn { V }
674 \cs_new_protected:Npn \_\_math_process_auxi:nn #1#2
675 {
676   \tl_gset:Nn \g__math_grabbed_env_tl {#2}
677   \tl_gset:Nn \g__math_grabbed_math_tl {#1}
678   \_\_math_process_auxii:nn {#2} {#1}
679 }
680 \cs_new_protected:Npn \_\_math_process_auxii:nn #1#2 { }
```

(End of definition for `\_\_math_process:nn`, `\_\_math_process_auxi:nn`, and `\_\_math_process_auxii:nn`.)

`\math_processor:n` A simple installer

```

681 \cs_new_protected:Npn \math_processor:n #1
682   { \cs_set_protected:Npn \_\_math_process_auxii:nn ##1##2 {#1} }
```

(End of definition for `\math_processor:n`. This function is documented on page 3.)

## 5.10 Content grabbing

`\__math_grab_dollar:w`  
`\__math_grab_dollar:n`

Top-level function to handle grabbing of inline math mode delimited by \$ tokens. We provide two different ways to do that: a token-by-token one that can be used everywhere, and a fast delimited one that does not work anywhere that the end \$ token may be hidden, most obviously in tabulars. The function here is therefore set up as a variable starting point.

683 `\cs_new_protected:Npn \__math_grab_dollar:w { \__math_grab_dollar_delim:w }`

After grabbing inline math material, there is again common processing independent of mechanism of collection.

684 `\cs_new_protected:Npn \__math_grab_dollar:n #1`  
685   {

We need to do processing first as this picks up “fake” math mode: that information is needed below.

686    `\__math_process:nn { math } {#1}`

We do not want math tagging in fakemath or when measuring, We also do not want math tagging if tagging has been suspended.

687    `\bool_lazy_any:nTF`  
688      {  
689        `{\legacy_if_p:n { measuring@ }}`  
690        `{ \l__math_fakemath_bool }`  
691        `{ \tl_if_blank_p:n {#1} }`  
692      }  
693      {  
694        `#1 $ % $`  
695      }  
696      {  
697        `\tag_socket_use:n {math/inline/begin} %end P-MC`  
698        `\tag_socket_use:nn {math/inline/formula/begin}{#1}`  
699        `$ % $`  
700        `\tag_socket_use:n {math/inline/formula/end}`  
701        `\tag_socket_use:n {math/inline/end} % restart P-MC`  
702      }  
703 }

(End of definition for `\__math_grab_dollar:w` and `\__math_grab_dollar:n`.)

`\__math_grab_dollar_delim:w`

Grab up to a single \$, for inline math mode, suppressing any processing if the token is `\m@th` found in the content.

704 `\cs_new_protected:Npn \__math_grab_dollar_delim:w #1 $ % $`  
705    { `\__math_grab_dollar:n {#1}`  }

(End of definition for `\__math_grab_dollar_delim:w`.)

`\__math_grab_dollardollar:w`

And for the classical TeX display structure.

706 `\cs_new_protected:Npn \__math_grab_dollardollar:w % $$`  
707    `#1 $$`  
708    {  
709      `\tl_if_blank:nF {#1}`

```

710      {
711          \__math_process:nn { equation* } {#1}
712          \socket_use:n {tagsupport/math/display/begin}
713          \socket_use:nn{tagsupport/math/display/formula/begin}{#1}
714      }
715      $$
716  }

```

The end code is added through a `\aftergroup` so we store it inside a command.

```

717 \cs_new_protected:Npn \__math_tag_dollardollar_display_end:
718  {
719      % \typeout{== tag dollarldollar display end}
720      % \ShowTagging{struct-stack}
721      \para_raw_end:

```

TODO why is that needed? where is para-tagging disabled?

```

722      \tagpdfparaOn
723      \l__math_tmpa_skip \lastskip
724      \socket_use:n{tagsupport/math/display/formula/end}
725      \penalty \postdisplaypenalty

```

This reinserts the below display skips. It must be doubled to get the right amount:

```

726      \skip_vertical:n { -\l__math_tmpa_skip * 2 }
727      %
728      \oendpe % this has no \end{...} to take care of it
729  }
730

```

*(End of definition for `\__math_grab_dollardollar:w`.)*

`\__math_grab_inline:w` Collect inline math content and deal with the need to move to math mode.

```

731 \cs_new_protected:Npn \__math_grab_inline:w % \
732     #1 \
733  {
734      \tl_if_blank:nF {#1}
735      {
736          $ #1 $
737      }
738      \bool_set_false:N \l__math_collected_bool
739  }

```

*(End of definition for `\__math_grab_inline:w`.)*

`\__math_grab_eqn:w` For the most common use of `\[/\]`: turn into an environment.

```

740 \cs_new_protected:Npn \__math_grab_eqn:w % \
741     #1 \
742  {
743      % \typeout{collected? = \bool_if:NTF \l__math_collected_bool {true}{false}}
744      \begin{equation*} #1 \end{equation*}
745  }

```

*(End of definition for `\__math_grab_eqn:w`.)*

## 5.11 Token-by-token inline grabbing

Grabbing inline math token-by-token is more involved. The mechanism here is essentially a simplified version of that originally seen in `collcell` and refined in `siunitx`. We make use of the fact that in math mode spaces are ignored, so we have to deal with only N-type tokens and groups. Furthermore, there is no need to look inside groups, so the only special cases are a small selection of N-type tokens.

---

`\l_math_grabbed_tl` For collection of the material piecewise.

746   `\tl_new:N \l_math_grabbed_tl`

---

`\l_math_grab_env_int` Needed to count up the number of nested environments encountered.

747   `\int_new:N \l_math_grab_env_int`

`\__math_grab_dollar_loop:` The lead-off here establishes a group: we need that as we will have to be careful in the way `\cr` is handled and ensure this is only manipulated whilst grabbing. The main loop is then started.

```
748 \cs_new_protected:Npn \__math_grab_dollar_loop:
749   {
750     \group_begin:
751       \tl_clear:N \l_math_grabbed_tl
752       \__math_grab_loop:
753   }
754 \cs_new_protected:Npn \__math_grab_loop:
755   {
756     \peek_remove_spaces:n
757     {
758       \peek_meaning:NTF \c_group_begin_token
759         { \__math_grab_loop_group:n }
760         { \__math_grab_loop_token:N }
761     }
762 }
```

(End of definition for `\__math_grab_dollar_loop:` and `\__math_grab_loop:..`)

`\__math_grab_loop_group:n` Handling of grabbed groups is pretty easy.

```
763 \cs_new_protected:Npn \__math_grab_loop_group:n #1
764   { \__math_grab_loop_store:n { #1 } }
765 \cs_new_protected:Npn \__math_grab_loop_store:n #1
766   {
767     \tl_put_right:Nn \l_math_grabbed_tl { #1 }
768     \__math_grab_loop:
769 }
```

(End of definition for `\__math_grab_loop_group:n` and `\__math_grab_loop_store:n`.)

`\__math_grab_loop_token:N` Filter out the special cases: for performance reasons, use a hash table approach rather than a loop (*cf. collcell*). The need to cover `\begin_{\mathord{\mathrm{U}}}` is that at the start of a cell, TeX will expand `\begin` but the L<sup>A</sup>T<sub>E</sub>X robust mechanism will mean this yields `\begin_{\mathord{\mathrm{U}}}`. If `\begin` were protected, that would not be needed.

```
\__math_grab_loop_\\begin_{\mathord{\mathrm{U}}}:
\__math_grab_loop_\\begin_{\mathord{\mathrm{U}}}:
\__math_grab_loop_\\end:
\__math_grab_loop_\\ignorespaces:
\__math_grab_loop_\\unskip:
\__math_grab_loop_\\textonly@unskip:
```

```

770 \cs_new_protected:Npn \__math_grab_loop_token:N #1
771 {
772     \cs_if_exist_use:cF
773         { __math_grab_loop_ \token_to_str:N #1 : }
774         { \__math_grab_loop_store:n {#1} }
775 }
776 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N $ : }
777 { \__math_grab_loop_end: }
778 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N \\ : }
779 {
780     \int_compare:nNnTF \l__math_grab_env_int = 0
781         { \__math_grab_loop_newline: }
782         { \__math_grab_loop_store:n {\\} }
783 }

```

In contrast to `colcell`, nesting is tracked by counting `\begin`/`\end` pairs: this is needed in case there is a tabular-like construct containing `\\"` inside a cell. As a result, the end-of-tabular can be detected without checking the name argument: if `\end` is encountered at nesting level 0, we've hit the end of a cell. In that case, end the row and leave the environment to clean up.

```

784 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N \begin : }
785 {
786     \int_incr:N \l__math_grab_env_int
787     \__math_grab_loop_store:n { \begin }
788 }
789 \cs_new_eq:cc { __math_grab_loop_ \token_to_str:N \begin \c_space_tl : }
790 { __math_grab_loop_ \token_to_str:N \begin : }
791 \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N \end : }
792 {
793     \int_compare:nNnTF \l__math_grab_env_int = 0
794     {
795         \__math_grab_loop_newline:
796         \end
797     }
798     {
799         \int_decr:N \l__math_grab_env_int
800         \__math_grab_loop_store:n { \end }
801     }
802 }
803 \tl_map_inline:nn { \ignorespaces \unskip \textonly@unskip }
804 {
805     \cs_new_protected:cpn { __math_grab_loop_ \token_to_str:N #1 : }
806     { \__math_grab_loop: }
807 }

```

(End of definition for `\__math_grab_loop_token:N` and others.)

`\__math_grab_loop_newline:`: To allow collection of tokens in the part of the `\halign` template after `#`, we need TeX to see the primitive with the loop token in the right place. That is done by re-defining `\cr` at present. Ideally there would be a socket in the definition of `tabular`, etc., to handle this: there is also the need to examine in interaction with `longtable`, which also redefines `\cr`.

```

808 \cs_new_protected:Npn \__math_grab_loop_newline:
809 {

```

```

810     \if_false: { \fi:
811     \cs_set_protected:Npn \cr
812     {
813         \__math_grab_loop:
814         \tex_cr:D
815     }
816     \if_false: } \fi:
817     \\
818 }
```

(End of definition for `\__math_grab_loop_newline`.)

`\__math_grab_loop_end`: Clean up and pass on.

```

819 \cs_new_protected:Npn \__math_grab_loop_end:
820 {
821     \exp_args:NNV \group_end:
822     \__math_grab_dollar:n \l__math_grabbed_tl
823 }
```

(End of definition for `\__math_grab_loop_end`.)

## 5.12 Marking math environments

A general mechanism for math mode environments that do not grab their content (*cf.* most `amsmath` environments).

`\l__math_env_name_tl` To allow us to carry out “special effects”

```
824 \tl_new:N \l__math_env_name_tl
```

Here we set up specialised handling of environments. The idea for the `arg-spec` key is that if an environment takes arguments, we don’t worry during the main grabbing. Rather, we remove the arguments from the grabbed content and forward only the payload. That is done by (ab)using `!tcmd`.

```

825 \keys_define:nn { __math }
826 {
827     arg-spec .code:n =
828     {
829         \ExpandArgs { c } \DeclareDocumentCommand
830             { __math_env \l__math_env_name_tl _aux: }
831             {#1}
832             { \__math_env_forward:w }
833     }
834 }
```

`\math_register_env:nn` Set up to capture environment content and make available.

```

\math_register_env:n
\math_register_env:n
\RegisterMathEnvironment
835 \cs_new_protected:Npn \math_register_env:nn #1#2
836 {
837     \tl_set:Nn \l__math_env_name_tl {#1}
838     \keys_set:nn { __math } {#2}
839     \cs_gset_eq:cc { __math_env_ #1 _begin: } {#1}
840     \cs_gset_eq:cc { __math_env_ #1 _end: } { end #1 }
841 %
```

```

842 \ExpandArgs { nne } \RenewDocumentEnvironment {#1} { b }
843 {
844     \exp_not:N \bool_if:NTF \exp_not:N \l__math_collected_bool
845     {
846         %
847         \typeout{==>B1}
848     }
849     %
850     \cs_if_exist:cTF { __math_env #1 _aux: }
851     {
852         \exp_not:c { __math_env #1 _aux: }
853         ##1 \exp_not:N \__math_env_end: {#1}
854     }
855     { \exp_not:N \__math_process:nn {#1} {##1} }
856     \exp_not:n { \Q@kernel@math@registered@begin }
857     \bool_set_true:N \exp_not:N \l__math_collected_bool
858 }
859 %
860 \exp_not:N \tracingall
861 \exp_not:c { __math_env_ #1 _begin: }
862 ####1
863 \exp_not:c { __math_env_ #1 _end: }
864 \exp_not:N \tracingnone
865 {
866 }
867 }
868
869 \cs_new_protected:Npn \math_register_halign_env:nn #1#2
870 {
871     \tl_set:Nn \l__math_env_name_tl {#1}
872     \keys_set:nn { __math } {#2}
873     \cs_gset_eq:cc { __math_env_ #1 _begin: } {#1}
874     \cs_gset_eq:cc { __math_env_ #1 _end: } { end #1 }
875 %
876 \ExpandArgs { nnee } \RenewDocumentEnvironment {#1} { b }
877 {
878     \exp_not:N \bool_if:NTF \exp_not:N \l__math_collected_bool
879     {
880         %
881         \typeout{==>B1}
882     }
883     %
884     \cs_if_exist:cTF { __math_env #1 _aux: }
885     {
886         \exp_not:c { __math_env #1 _aux: }
887         ##1 \exp_not:N \__math_env_end: {#1}
888     }
889     { \exp_not:N \__math_process:nn {#1} {##1} }
890     \exp_not:n { \Q@kernel@math@registered@begin }
891     \bool_set_true:N \exp_not:N \l__math_collected_bool
892 }
893 %
894 \exp_not:N \tracingall
895 \exp_not:c { __math_env_ #1 _begin: }
896 ####1

```

```

896 %           \exp_not:N \tracingnone
897 }
898 {
899     \exp_not:c { __math_env_ #1 _end: }
900 }
901 }

TODO: the following command is neither documented nor used. Is is needed?
902 \cs_new_protected:Npn \math_register_odd_env:nn #1#2
903 {
904     \tl_set:Nn \l__math_env_name_tl {#1}
905     \keys_set:nn { __math } {#2}
906     \cs_gset_eq:cc { __math_env_ #1 _begin: } {#1}
907     \cs_gset_eq:cc { __math_env_ #1 _end: } { end #1 }
908 %
909     \ExpandArgs { nnee } \RenewDocumentEnvironment {#1} { b }
910     {
911         \exp_not:N \bool_if:NTF \exp_not:N \l__math_collected_bool
912         {
913             \typeout{==>B1}
914         }
915         {
916             \typeout{==>B2}
917             \cs_if_exist:cTF { __math_env #1 _aux: }
918             {
919                 \exp_not:c { __math_env #1 _aux: }
920                 ##1 \exp_not:N \__math_env_end: {#1}
921             }
922             { \exp_not:N \__math_process:nn {#1} {##1} }
923             \exp_not:n { \Q@kernel@math@registered@begin }
924             \bool_set_true:N \exp_not:N \l__math_collected_bool
925         }
926 %
927         \exp_not:N \tracingall
928         \exp_not:c { __math_env_ #1 _begin: }
929         ##1
930     }
931     {
932         \exp_not:c { __math_env_ #1 _end: }
933 % needed if we don't have $$...$$
934         \exp_not:n { \typeout{--> \Q@kernel@math@registered@end } }
935         \exp_not:n { \Q@kernel@math@registered@end }
936     }
937
938
939 % FMi: compare with block change!
940 %
941 % \DeclareRobustCommand*\begin[1]{%
942 %   \UseHook{env/#1/before}%
943 %   \Q@ifundefined{#1}%
944 %     {\def\reserved@a{\Q@latex@error{Environment #1 undefined}\Q@eha}}%
945 %     {\def\reserved@a{\def\currenvir{#1}}%
946 %       \edef\currenvline{\on@line}%
947 %       \Q@execute@begin@hook{#1}}%

```

```

948 %           \csname #1\endcsname} }%
949 %   \ignorespaces
950 % \begingroup
951 % \endgroup % tmp!!! is it ok to drop this here?
952 % \reserved@a}
953
954
955 \cs_new:Npn \@kernel@math@registered@begin {
956 %   \ShowTagging{struct-stack}
957 % \typeout{==>A1}\ShowTagging{struct-stack,mc-current}
958   \mode_if_vertical:TF
959   {
960     \legacy_if:nTF { \endpe }
961     { \legacy_if_set_false:n { \endpe } }
962     { \__block_list_beginpar_vmode: }
963 %
964 %   \typeout{==>~ at:~ \g__tag_struct_tag_tl}
965 %
966   \tag_if_active:T
967   {
968     \exp_args:Nno\str_if_eq:nnF \g__tag_struct_tag_tl { \l__tag_para_main_tag_tl }
969     {
970       \typeout{==>A2}
971       \__block_beginpar_vmode:
972     } % needs correction!
973   }
974 }
975 {
976 %   \typeout{==>A3}
977   \__tag_tool_close_P:
978 }
979 \socket_use:nn{tagsupport/math/display/formula/begin}{}
980 \tagpdfparaOff
981 % \typeout{==>MC1}\ShowTagging{mc-current}
982 }

983 \cs_new:Npn \@kernel@math@registered@end {
984 %   \typeout{==>MC2}\ShowTagging{mc-current}
985   \para_raw_end:
986   \tagpdfparaOn
987   \socket_use:n{tagsupport/math/display/formula/end}
988 %   \typeout{==>MC3}\ShowTagging{mc-current}
989   \endtrue
990 }
991 }

992 \cs_new_protected:Npn \math_register_env:n #1
993   { \math_register_env:nn {#1} { } }
994
995 \NewDocumentCommand \RegisterMathEnvironment { O{} m }
996   { \math_register_env:nn {#2} {#1} }

(End of definition for \math_register_env:nn, \math_register_env:n, and \RegisterMathEnvironment.
These functions are documented on page 3.)
```

\\_\_math\_env\_forward:w

```

998 \cs_new_protected:Npn \__math_env_forward:w #1 \__math_env_end: #2
999 { \__math_process:nn {#2} {#1} }

```

(End of definition for `\__math_env_forward:w`.)

## 5.13 Document commands

Add one more here: `displaymath`, which is equivalent to `\[ , \]` and hence to the basic `equation*`.  
Added in more recent branch.

```

\equation
\__math_equation_begin:
\equation*
\__math_equation_star_begin:
\endequation
\__math_equation_end:
\endequation*
\__math_equation_star_end:

```

These environments are not set up by `amsmath` to collect their body, so we do that here. This has to be done *after* we can be sure `amsmath` is loaded.

Note that with `amsmath` loaded, `equation*` and `equation` are the two basics: they are used to define the other single-row display environments, etc.

```

1000 \tl_gput_right:Nn \@kernel@before@begindocument
1001 {
1002     \math_register_env:n { equation }
1003     \math_register_env:n { equation* }
1004 % at the moment register_env can only do display math
1005 %     \math_register_env:n { math }
1006     \RenewDocumentEnvironment{math} {b}{##1}{}
1007 % and this one doesn't work either
1008 %     \math_register_env:n { displaymath }
1009     \RenewDocumentEnvironment{displaymath} {b}{\[#1\]}{}
1010 }

```

(End of definition for `\equation` and others. These functions are documented on page ??.)

- \(\backslash\)( If math mode has not been collected, we need to do that; otherwise, worry about whether
- \(\backslash\)\) we are in math mode or not. The closing command here can only occur inside a collected math block: otherwise it will be simply used as a delimiter.

```

1011 \cs_gset_protected:Npn \(\ % \)
1012 {
1013     \bool_if:NTF \l__math_collected_bool
1014     {
1015         \mode_if_math:TF
1016         { \@badmath }
1017         { $ }
1018     }
1019     {
1020         \__math_grab_inline:w
1021     }
1022 } \% \
1023 \cs_gset_protected:Npn \
1024 {
1025     \mode_if_math:TF
1026     { $ }
1027     { \@badmath }
1028 }

```

(End of definition for `\(` and `\)`. These functions are documented on page ??.)

- \[ Again, we need to watch for when amsmath is loaded after this code. The flag usage here is to cover the case where \[/\] is hidden inside another environment. In this case the grabbing happens on the outer level and should not be repeated.

```

1029 \tl_gput_right:Nn \@kernel@before@begindocument
1030 {
1031   \cs_gset_protected:Npn \[ % \]
1032   {
1033     \__math_grab_eqn:w
1034     \% \bool_if:NTF \l__math_collected_bool
1035     { \begin{ equation* } }
1036     { \__math_grab_eqn:w }
1037   } % \[
1038   \cs_gset_protected:Npn \
1039   {
1040     \@badmath
1041     \% \bool_if:NTF \l__math_collected_bool
1042     { \end{ equation* } }
1043     { \@badmath }
1044   }
1045 }
```

(End of definition for \[ and \]. These functions are documented on page ??.)

why does ensuremath need handling at all?

Indeed! Currently, this is setup to process the math that it has anyways already captured as its argument; thus it is more efficient than leaving the capture to be repeated by the \everymath

A bit of nesting fun to make sure we collect only if required.

```

1046 \% \cs_gset_protected:Npn \ensuremath #1
1047 \% {
1048 \%   \mode_if_math:TF
1049 \%   {#1}
1050 \%   {
1051 \%     \bool_if:NTF \l__math_collected_bool
1052 \%     { \@ensuredmath {#1} }
1053 \%     {
1054 \%       \bool_set_true:N \l__math_collected_bool
1055 \%       \__math_process:nn { math } {#1}
1056 \%       \@ensuredmath {#1}
1057 \%       \bool_set_false:N \l__math_collected_bool
1058 \%     }
1059 \%   }
1060 \% }
```

(End of definition for \ensuremath. This function is documented on page ??.)

## 5.14 \everymath and \everydisplay

The business end for grabbing inline math and “raw” T<sub>E</sub>X display. Most display math mode is actually handled elsewhere, as we have macro control.

```

1061
1062 \exp_args:No \tex_everymath:D
1063 {
1064   \tex_the:D \tex_everymath:D
1065   \bool_if:NF \l__math_collected_bool
1066   {
1067     \bool_set_true:N \l__math_collected_bool
```

```

1068         \__math_grab_dollar:w
1069     }
1070 }
1071
1072 \exp_args:No \tex_everydisplay:D
1073 {
1074     \tex_the:D \tex_everydisplay:D
1075     \iftrue % this may have to be a settable flag!
1076     % \typeout{==>~ in~ everydisplay}

```

flipping the `\belowdisplay` values is done so that we get (assumption) a negative skip and not make the page bigger then we take that out, then we add the tagging code (in `\__math_tag_dollardollar_display_end`) and then we put a real `\postdisplaypenalty` in and the right skip (of which we don't know if it is short or a normal `\belowdisplayskip`). This might need some refinement if that skip is actually negative from the start (not sure it ever is and is worth bothering about)

```

1077     \skip_set:Nn \belowdisplayskip {-\belowdisplayskip}
1078     \skip_set:Nn \belowdisplayshortskip {-\belowdisplayshortskip}
1079     \int_set:Nn \postdisplaypenalty {10000}
1080     \group_insert_after:N \__math_tag_dollardollar_display_end:
1081     \fi
1082     \bool_if:NF \l__math_collected_bool
1083     {
1084         \bool_set_true:N \l__math_collected_bool
1085         \__math_grab_dollardollar:w
1086     }
1087 }

```

## 5.15 Modifying kernel environments

We need to cover this even though it is, of course, not encouraged.

```

1088 \math_register_env:n { eqnarray }
1089 \math_register_env:n { eqnarray* }

```

Tabulars currently contain a \$ that shouldn't trigger math tagging.

```

1090 \RequirePackage{array}
1091 \tl_if_in:NnT\@tabular{$}
1092 {
1093     \def\@tabular{%
1094         \leavevmode
1095         \UseTaggingSocket{tbl/hmode/begin}%
1096         \hbox \bgroup
1097         \bool_set_true:N \l__math_collected_bool
1098         $
1099         \bool_set_false:N \l__math_collected_bool
1100         \col@sep\@tabcolsep \let\dollarbegin\begin{group}
1101                                         \let\dollarend\endgroup

```

A proper switching mechanism is needed: for the present, do directly.

```

1102     \cs_set_protected:Npn \__math_grab_dollar:w { \__math_grab_dollar_loop: }
1103     \@tabarray
1104 }

```

`\__math_m@th:` Handle non-math use of math mode. At present nesting isn't supported as `\m@th` pops up in a few places that *are* math mode!

```

1105 \cs_new_eq:NN \__math_m@th: \m@th
1106 \cs_gset_protected:Npn \m@th
1107 {
1108     \bool_set_true:N \l__math_collected_bool
1109     \__math_m@th:
1110 }

```

(End of definition for `\__math_m@th:` and `\m@th`. This function is documented on page ??.)

## 5.16 Disable math grabbing in the begindocument hook

For example amsart uses math to measure text there.

```

1111 \tl_gput_right:Nn\@kernel@before@begindocument
1112 {
1113     \bool_set_true:N\l__math_collected_bool
1114 }
1115 \tl_gput_right:Nn\@kernel@after@begindocument
1116 {
1117     \bool_set_false:N\l__math_collected_bool
1118 }

```

## 5.17 Modifying amsmath

Mark up all of the display environments as the content is captured anyway. We then use an internal macro in each environment type to insert the processing code. Each of these is slightly different, so we cannot use a simple loop here. The test for `\split@tag` is required as the `split` environment internally uses `gather` when not within an `amsmath` environment, for example inside `equation`. Without the precaution, we'd get two copies of the grabbed math, the second of which would start with `\split@tag`.

```

1119
1120
1121
1122 \tl_gput_right:Nn \@kernel@before@begindocument {
1123 %
1124 \renewenvironment{gather*}{%
1125     \start@gather\st@rredtrue
1126 }
1127 {%
1128 % this redirection doesn't work if we alter "gather"!
1129 % \endgather
1130 % so replace it with its real meaning
1131 \math@cr \black@\totwidth@\egroup
1132 $$\ignorespacesafterend
1133 }

1134 \def\common@align@ending {
1135     \math@cr \black@\totwidth@
1136     \egroup
1137     \ifingather@
1138         \restorealignstate@
1139         \egroup

```

```

1140     \nonumber
1141     \ifnum0='{\fi\iffalse}\fi
1142 \else
1143   $$%
1144 \fi
1145 \ignorespacesafterend
1146 }
1147 \renewenvironment{alignat}{%
1148   \start@align\z@\st@rredfalse
1149 }{%
1150   \common@align@ending
1151 }
1152 \renewenvironment{alignat*}{%
1153   \start@align\z@\st@rredtrue
1154 }{%
1155   \common@align@ending
1156 }
1157 \renewenvironment{xalignat}{%
1158   \start@align\@ne\st@rredfalse
1159 }{%
1160   \common@align@ending
1161 }
1162 \renewenvironment{xalignat*}{%
1163   \start@align\@ne\st@rredtrue
1164 }{%
1165   \common@align@ending
1166 }
1167 \renewenvironment{xxalignat}{%
1168   \start@align\tw@\st@rredtrue
1169 }{%
1170   \common@align@ending
1171 }
1172 \renewenvironment{align}{%
1173   \start@align\@ne\st@rredfalse\m@ne
1174 }{%
1175   \common@align@ending
1176 }
1177 \renewenvironment{align*}{%
1178   \start@align\@ne\st@rredtrue\m@ne
1179 }{%
1180   \common@align@ending
1181 }
1182 \renewenvironment{flalign}{%
1183   \start@align\tw@\st@rredfalse\m@ne
1184 }{%
1185   \common@align@ending
1186 }
1187 \renewenvironment{flalign*}{%
1188   \start@align\tw@\st@rredtrue\m@ne
1189 }{%
1190   \common@align@ending
1191 }
1192 %
1193 \renewenvironment{multiline*}{\start@multline\st@rredtrue}

```

```

1194 {%
1195   \iftagsleft@ \exp\lendmultline@ \else \exp\rendmultline@ \fi
1196   \ignorespacesafterend
1197 }

Also for false?

1198 \def\measuring@true{\let\ifmeasuring@\iftrue\tag_stop:}
1199 %
1200   \math_register_halign_env:nn {align}={}
1201   \math_register_halign_env:nn {align*}={}
1202   \math_register_halign_env:nn {alignat}={}
1203   \math_register_halign_env:nn {alignat*}={}
1204   \math_register_halign_env:nn {flalign}={}
1205   \math_register_halign_env:nn {flalign*}={}
1206   \math_register_halign_env:nn {gather}={}
1207   \math_register_halign_env:nn {gather*}={}
1208   \math_register_halign_env:nn {multiline}={}
1209   \math_register_halign_env:nn {multiline*}={}
1210   \math_register_halign_env:nn {xalignat}={}
1211   \math_register_halign_env:nn {xalignat*}={}
1212   \math_register_halign_env:nn {xxalignat}={}
1213 %
1214 \cnamedef{maketag @ @ @} #1{%
1215 %   \typeout{--->maketag @ @ @}
1216   \ifmeasuring@
1217     \hbox{\m@th\normalfont#1}%
1218   \else
1219     \tagmcend \tagstructbegin{tag=Lbl}%
1220     \tagmcbegin{tag=Lbl}%
1221     \hbox{\m@th\normalfont#1}%
1222     \tagmcend \tagstructend \tagmcbegin{}%
1223   \fi
1224 }

1225 \cnamedef{math@cr @ @ @ gather}{%
1226   \ifst@rred\nonumber\fi
1227   &\relax
1228   \make@display@tag
1229 %
1230   \maybestartnewformulatag
1231 %
1232   \ifst@rred\else\global\eqnswtrue\fi
1233   \global\advance\row@\@ne
1234   \cr
1235 }

1236 \cnamedef{math@cr @ @ @ align}{%
1237   \ifst@rred\nonumber\fi
1238   \if@eqnsw \global\tag@true\fi
1239   \global\advance\row@\@ne
1240   \add@amps\maxfields@%
1241   \omit
1242   \kern-\alignsep@
1243   \iftag@
1244     \setboxz@h{\@ignstrut@\make@display@tag}%

```

```

1245     \place@tag
1246     \fi
1247 %
1248     \maybestartnewformulatag
1249 %
1250     \ifst@rred\else\global\eqnswtrue\fi
1251     \global\lineht@\z@
1252     \cr
1253 }
1254 \def\restore@math@cr{\@namedef{math@cr }{ }{ }{
1255 %
1256     \maybestartnewformulatag
1257 %
1258     \cr}}
1259 \restore@math@cr
1260 }

```

(End of definition for `\__math_amsmath_align@nn` and others. These functions are documented on page ??.)

`\__math_split_at_nl:NN` This splits grabbed math at newlines.

```

1261 \cs_new:Npn \__math_split_at_nl:NN #1#2 {
1262     \tl_set:Nf \l__math_tmpa_tl {
1263         \exp_after:wN \__math_split_at_nl_first:w #1 \\ \q_nil \\ \s_stop }
1264     \exp_after:wN \__math_split_at_nl_aux:nnNN \l__math_tmpa_tl #1 #2
1265 }

```

and the auxiliary commands

```

1266 \cs_new:Npn \__math_split_at_nl_first:w #1 \\ #2 \\ #3 \s_stop
1267 {
1268     \quark_if_nil:nTF {#2}
1269     { {#1} { } }
1270     {
1271         \__math_split_chk_if_begin:ww #1 \begin \q_nil \s_mark
1272         #2 \\ #3 \s_stop
1273     }
1274 }
1275
1276 \cs_new_protected:Npn \__math_split_at_nl_aux:nnNN #1 #2 #3 #4
1277 {
1278     \tl_gset:Nn #4 {#1}
1279     \tl_gset:Nn #3 {#2}
1280 }
1281
1282 \cs_new:Npn \__math_split_chk_if_begin:ww
1283     #1 \begin #2 #3 \s_mark #4 \\ \q_nil \\ \s_stop
1284 {
1285     \quark_if_nil:nTF {#2}
1286     { {#1} {#4} }
1287     {
1288         \exp_after:wN \__math_split_collect_one_end:w
1289         \__math_split_cleanup_begin_q_nil:w #1 \begin{#2} #3 \\ #4 \s_stop
1290         { } { 1 }
1291     }

```

```

1292     }
1293
1294 \cs_new:Npn \__math_split_cleanup_begin_q_nil:w #1 \begin {q_nil} {#1}
1295
1296 \cs_new:Npn \__math_split_collect_one_end:w #1 \end #2 #3 \s_stop #4 #5
1297 {
1298     \exp_args:Nf \__math_split_check_count_begins:nnnn
1299     { \__math_split_count_begins:n { #4 #1 } } {#5}
1300     { #4 #1 \end{#2} } {#3}
1301 }
1302 \cs_new:Npn \__math_split_count_begins:n #1
1303 { \int_eval:n { 0 \__math_split_count_begins:w #1 \begin {q_nil} } }
1304
1305 \cs_new:Npn \__math_split_count_begins:w #1 \begin #2
1306 { \quark_if_nil:nF {#2} { +1 \__math_split_count_begins:w } }
1307
1308 \cs_new:Npn \__math_split_check_count_begins:nnnn #1 #2 #3 #4
1309 {
1310     \int_compare:nNnTF {#1} = {#2}
1311     {
1312         \exp_last_unbraced:Nf \__math_split_final_cleanup:nn
1313         { \__math_split:n { \__math_split_guard:n {#3} #4 } }
1314     }
1315     {
1316         \exp_args:No \use_i_i_i:nn
1317         { \exp_after:wN { \int_value:w \int_eval:n { #2 + 1 } } }
1318         { \__math_split_collect_one_end:w #4 \s_stop {#3} }
1319     }
1320 }
1321 \cs_new:Npn \__math_split_final_cleanup:nn #1 #2
1322 {
1323     \exp:w \__math_split_final_cleanup:w #1
1324         \__math_split_guard:n \q_nil \s_mark { }
1325     {#2}
1326 }
1327 \cs_new:Npn \__math_split_final_cleanup:w #1 \__math_split_guard:n #2 #3 \s_mark #4
1328 {
1329     \quark_if_nil:nTF {#2}
1330     { \exp_end: { #4 #1 } }
1331     { \__math_split_final_cleanup:w #3 \s_mark { #4 #1 #2 } }
1332 }
1333
1334 \cs_new:Npn \__math_split:n #1 {
1335     \__math_split_at_nl_first:w #1 \\ \q_nil \\ \s_stop }
1336
1337 % this looks unused.
1338 %\NewDocumentCommand \splitnl { mm +m }
1339 % {
1340 %     \tl_set:Nf \l__math_tmpa_tl { \split:n {#3} }
1341 %     \show \l__math_tmpa_tl
1342 %     \exp_after:wN \__splitnl_aux:nnNN \l__math_tmpa_tl #1 #2
1343 % }

```

(End of definition for `\__math_split_at_nl:NN`.)

```

\maybestartnewformulatag

1344
1345 \newif\if@subformulas
1346 \tl_new:N \result
1347
1348 \cs_new_protected:Npn\grabaformulaapartandstart {
1349   \__math_split_at_nl:NN \g__math_grabbed_math_tl \result
1350   \typeout{====>first-result=\meaning\result}
1351   \typeout{====>first-tmpmathcontent=\meaning\g__math_grabbed_math_tl}
1352   \tl_if_empty:NTF \g__math_grabbed_math_tl
1353   {
1354     \typeout{====>formula~ has~ no~ subparts}
1355     \global\@subformulasfalse
1356   }
1357   {
1358     \typeout{====>formula~ has~ subparts}
1359     \global\@subformulastrue
1360     \edef\resulttitle{\g__math_grabbed_env_tl\space (part)}
1361     \tagstructbegin{tag=Formula,

```

For now we don't put real content in /alt or /ActualText on subformulas but we add a short text to satisfy the pdf/ua-2 validator

```

1362 %      alt=\result,
1363 %      alt = subformula,
1364 %      title-o=\resulttitle
1365   }
1366   }
1367   \tagmcbegin{}
1368 }

1369
1370 \cs_new_protected:Npn\grabaformulaapartandmayberestart {
1371   \__math_split_at_nl:NN \g__math_grabbed_math_tl \result
1372   \typeout{====>result=\meaning\result}
1373   \typeout{====>ttmpmathcontent=\meaning\g__math_grabbed_math_tl}
1374 % \tl_if_empty:NTF \g__math_grabbed_math_tl
1375 %
1376 %      \typeout{====>ttmpmathcontent=empty}
1377 %
1378 %
1379 %      \typeout{====>ttmpmathcontent=not-empty}
1380   \edef\resulttitle{\g__math_grabbed_env_tl\space (part)}
1381   \tagstructbegin{tag=Formula,
1382     alt=\result,
1383     title-o=\resulttitle
1384   }
1385 %
1386   \tagmcbegin{}
1387 }

```

(End of definition for \maybestartnewformulatag. This function is documented on page ??.)

```

1388 \def\maybestartnewformulatag {
1389 \if@subformulas
1390   \ifmeasuring@\else
1391 %

```

```

1392     \tl_if_empty:N \g__math_grabbed_math_tl
1393     {
1394         \tagmcend
1395         \tagstructend
1396         \grabaformula part and maybe restart
1397     }
1398     \fi
1399 \fi
1400 }

```

The breqn packages changes catcodes and that isn't yet covered by our mechanism.

```

1401 \%AddToHook{package/breqn/after}%
1402 % \typeout{==>~ in~ hook}
1403 % \math_register_halign_env:nn {dmath}={}
1404 % \math_register_halign_env:nn {dgroup*}={}
1405 %
1406 \ExplSyntaxOff
1407 <@=›
1408 </kernel>

```

# Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
\# . . . . .	72, 342
\% . . . . .	73
\( . . . . .	731
\( . . . . .	<u>1011</u>
\) . . . . .	732
\) . . . . .	<u>1011</u>
@@ commands:	
\l_@@_collected_bool . . . . .	3, 7
\l_@@_fakemath_bool . . . . .	8
\[ . . . . .	<u>740</u> , 1009
\[ . . . . .	<u>9</u> , <u>28</u> , <u>35</u> , <u>36</u> , <u>1029</u>
\\" . . . . .	<u>242</u> , <u>243</u> , <u>244</u> , <u>245</u> , <u>246</u> , <u>247</u> , <u>778</u> , <u>782</u> , <u>817</u> , <u>1263</u> , <u>1266</u> , <u>1272</u> , <u>1283</u> , <u>1289</u> , <u>1335</u>
\{ . . . . .	70
\} . . . . .	71
\] . . . . .	<u>741</u> , 1009
\] . . . . .	<u>9</u> , <u>28</u> , <u>35</u> , <u>36</u> , <u>1029</u>
<b>A</b>	
actual+source (plug) . . . . .	<u>495</u>
\AddToHook . . . . .	7, <u>9</u> , <u>121</u> , <u>208</u> , <u>278</u> , <u>323</u> , <u>364</u> , <u>381</u> , <u>1401</u>
\advance . . . . .	<u>1233</u> , <u>1239</u>
\aftergroup . . . . .	<u>28</u>
<b>B</b>	
alt+source (plug) . . . . .	<u>510</u>
\AssignSocketPlug . . . . .	<u>253</u> , <u>254</u> , <u>255</u> , <u>256</u> , <u>260</u> , <u>321</u> , <u>322</u> , <u>360</u> , <u>361</u> , <u>362</u> , <u>363</u>
\AtBeginDocument . . . . .	<u>663</u>
\begin . . . . .	<u>29</u> , <u>30</u> , <u>471</u> , <u>489</u> , <u>744</u> , <u>784</u> , <u>787</u> , <u>789</u> , <u>790</u> , <u>941</u> , <u>1035</u> , <u>1271</u> , <u>1283</u> , <u>1289</u> , <u>1294</u> , <u>1303</u> , <u>1305</u>
\begingroup . . . . .	<u>69</u> , <u>145</u> , <u>160</u> , <u>176</u> , <u>950</u> , <u>1100</u>
\belowdisplay . . . . .	<u>37</u>
\belowdisplayshortskip . . . . .	<u>1078</u>
\belowdisplayskip . . . . .	<u>37</u> , <u>1077</u>
\bgroup . . . . .	<u>1096</u>
block internal commands:	
\__block_beginpar_vmode: . . . . .	<u>971</u>
\__block_list_beginpar_vmode: . . .	<u>962</u>
bool commands:	
\bool_gset_true:N . . . . .	<u>252</u> , <u>309</u> , <u>350</u>
\bool_if:NTF . . . . .	<u>62</u> , <u>357</u> , <u>532</u> , <u>569</u> , <u>574</u> , <u>588</u> , <u>596</u> , <u>743</u> , <u>844</u> , <u>878</u> , <u>911</u> , <u>1013</u> , <u>1034</u> , <u>1041</u> , <u>1051</u> , <u>1065</u> , <u>1082</u>
\bool_lazy_any:nTF . . . . .	<u>687</u>
\bool_new:N . . . . .	<u>10</u> , <u>11</u> , <u>37</u> , <u>38</u> , <u>39</u> , <u>40</u> , <u>41</u> , <u>42</u>
\bool_set_false:N . . . . .	<u>738</u> , <u>1057</u> , <u>1099</u> , <u>1117</u>

\bool_set_true:N	669, 857, 891, 924, 1054, 1067, 1084, 1097, 1108, 1113
bool internal commands:	
\l__math_collected_bool	9, 10, 738, 743, 844, 857, 878, 891, 911, 924, 1013, 1034, 1041, 1051, 1054, 1057, 1065, 1067, 1082, 1084, 1097, 1099, 1108, 1113, 1117
\l__math_fakemath_bool	9, 11, 669, 690
box commands:	
\box_new:N	333
box internal commands:	
\l__math_tmpa_box	333, 336
\boxed	7
C	
char commands:	
\char_set_catcode_other:N	70, 71, 72, 73, 342
clist commands:	
\clist_map_inline:Nn	344
\clist_new:N	50
\clist_put_right:Nn	51
\cr	811, 1234, 1252, 1258
cs commands:	
\cs_generate_variant:Nn	394, 551, 673
\cs_gset_eq:NN	839, 840, 873, 874, 906, 907
\cs_gset_protected:Npn	1011, 1023, 1031, 1038, 1046, 1106
\cs_if_eq:NNTF	145, 160, 176
\cs_if_exist:NTF	850, 884, 917
\cs_if_exist_use:N	598
\cs_if_exist_use:NTF	772
\cs_new:Npn	264, 955, 984, 1261, 1266, 1282, 1294, 1296, 1302, 1305, 1308, 1321, 1327, 1334
\cs_new_eq:NN	789, 1105
\cs_new_protected:Npn	22, 53, 68, 76, 250, 334, 385, 641, 652, 664, 674, 680, 681, 683, 684, 704, 706, 717, 731, 740, 748, 754, 763, 765, 770, 776, 778, 784, 791, 805, 808, 819, 835, 869, 902, 993, 998, 1276, 1348, 1370
\cs_set:Npn	123, 135
\cs_set_eq:NN	343
\cs_set_protected:Npn	682, 811, 1102
\csname	948
D	
\DeclareDocumentCommand	829
\DeclareMathEnvironment	8
\DeclareRobustCommand	941
E	
\def	944, 945, 1093, 1134, 1198, 1254, 1388
default (plug)	419, 441, 450, 528, 613
\displaylines	8
F	
\fi	203, 624, 1081, 1141, 1144, 1195, 1223, 1226, 1232, 1237, 1238, 1246, 1250, 1398, 1399
fi commands:	
\fi:	810, 816
file commands:	
\file_if_exist:nTF	118, 346
\file_input:n	349

\gdef .....	133
\global .....	1232, 1233, 1238, 1239, 1250, 1251, 1355, 1359
\grabaformula part and maybe restart .....	1370, 1396
\grabaformula part and start .....	616, 1348
group commands:	
\group_begin: .....	750
\c_group_begin_token .....	758
\group_end: .....	821
\group_insert_after:N .....	1080
	H
\hbox .....	1096, 1217, 1221
hbox commands:	
\hbox_set:Nn .....	336
\hfil .....	142, 156, 171, 173
\hskip .....	143, 158, 174
	I
if commands:	
\if_false: .....	810, 816
\ifcase .....	141
\iffalse .....	1141
\ifnum .....	1141
\iftrue .....	1075, 1198
\ignorespaces .....	803
\ignorespacesafterend .....	1132, 1145, 1196
int commands:	
\int_compare:nNnTF .....	391, 780, 793, 1310
\int_decr:N .....	799
\int_eval:n .....	1303, 1317
\int_gincr:N .....	56, 59, 558, 573, 576
\int_incr:N .....	786
\int_new:N .....	45, 46, 47, 48, 49, 382, 383, 747
\int_set:Nn .....	257, 389, 1079
\int_use:N .....	108, 368, 370, 372, 374, 376, 384
\int_value:w .....	1317
int internal commands:	
\g_math_AF_attached_int .....	11
\g_math_AF_found_int .....	11
\g_math_AF_total_int .....	11
\l_math_grab_env_int .....	29, 747, 780, 786, 793, 799
\g_math_math_total_int .....	11, 47, 108, 372, 558
\g_math_mathchoice_int .....	19, 382
\g_math_mathml_AF_attached_int .....	11, 49, 376, 576
\g_math_mathml_AF_found_int .....	11, 48, 374, 573
	G
\gdef .....	11, 46, 59, 370
\g_math_mathml_total_int .....	11, 45, 56, 368
\l_math_mathstyle_int .....	382, 389
\g_math_mml_int .....	11
\g_math_mml_total_int .....	11
\intertext .....	8
iow commands:	
\iow_close:N .....	282, 327
\iow_new:N .....	261, 312
\iow_newline: .....	83, 85, 90, 92, 107, 109, 111, 113
\iow_now:Nn .....	263, 268, 280, 297, 317, 325
\iow_open:Nn .....	262, 313
\iow_term:n .....	366, 367, 368, 370, 372, 374, 376
iow internal commands:	
\g_math_luamml_iow .....	261, 262, 263, 268, 280, 282
\g_math_writedummy_iow .....	297, 310, 312, 313, 317, 325, 327
	K
\kern .....	1242
keys commands:	
\keys_define:nn .....	286, 305, 395, 825
\keys_set:nn .....	838, 872, 905
	L
\lastskip .....	723
\LaTeXe .....	7, 8
\leavevmode .....	1094
legacy commands:	
\legacy_if:nTF .....	666, 960
\legacy_if_p:n .....	689
\legacy_if_set_false:n .....	961
\let .....	1100, 1101, 1198
\ltxlabmathdate .....	4
\ltxlabmathversion .....	5
luamml commands:	
\luamml_flag_process: .....	277
\luamml_flag_save:nn .....	151, 166, 182
luamml internal commands:	
\__luamml_array_finalize_array: .....	131
\__luamml_array_finalize_col:w .....	153, 168, 184
\__luamml_array_init_col: .....	149, 164, 180
\__luamml_array_save_array: .....	126
\l__luamml_pretty_int .....	257
\__luamml_register_output_hook:N .....	276
	M
math commands:	
\math_processor:n .....	3, 681, 681

```

\math_register_env:n .... 3, 835,
993, 1002, 1003, 1005, 1008, 1088, 1089
\math_register_env:nn .....
..... 3, 835, 835, 994, 997
\math_register_halign_env:nn ...
..... 869, 1200, 1201, 1202,
1203, 1204, 1205, 1206, 1207, 1208,
1209, 1210, 1211, 1212, 1403, 1404
\math_register_odd_env:nn .... 902
math internal commands:
\math_AF_html_reader:w .... 68, 343
\math_AF_html_reader_verb:w 74, 76
\math_AF_mml:nnnn ..... 53, 53, 78
\math_AF_process_mathml_files:
..... 333, 334, 381
\math_amsmath_align@:nn .... 1119
\math_amsmath_gather@:n .... 1119
\math_amsmath_multline@:n .. 1119
\math_env_end: ... 853, 887, 920, 998
\math_env_forward:w . 832, 998, 998
\math_equation_begin: ..... 1000
\math_equation_end: ..... 1000
\math_equation_star_begin: . 1000
\math_equation_star_end: .. 1000
\math_grab_dollar:n .....
..... 683, 684, 705, 822
\math_grab_dollar:w .....
..... 683, 683, 1068, 1102
\math_grab_dollar_delim:w .....
..... 683, 704, 704
\math_grab_dollar_loop: .....
..... 748, 748, 1102
\math_grab_dollardollar:w .....
..... 706, 706, 1085
\math_grab_eqn:w 740, 740, 1033, 1036
\math_grab_inline:w 731, 731, 1020
\math_grab_loop: .....
..... 748, 752, 754, 768, 806, 813
\math_grab_loop_$: ..... 770
\math_grab_loop_\\: ..... 770
\math_grab_loop_\begin_: .... 770
\math_grab_loop_\begin: ..... 770
\math_grab_loop_\end: ..... 770
\math_grab_loop_\ignorespaces: 770
\math_grab_loop_\textonly@unskip:
..... 770
\math_grab_loop_\unskip: .... 770
\math_grab_loop_end: . 777, 819, 819
\math_grab_loop_group:n .....
..... 759, 763, 763
\math_grab_loop_newline: .....
..... 781, 795, 808, 808
\math_grab_loop_store:n .....
.... 763, 764, 765, 774, 782, 787, 800
\math_grab_loop_token:N .....
..... 760, 770, 770
\math_luamml_activate_write: ..
..... 213, 225, 250
\math_luamml_output_hook:n 264, 276
\math_m@th: ..... 1105, 1105, 1109
\math_process:nn .... 664, 664,
673, 686, 711, 855, 889, 922, 999, 1055
\math_process_auxi:nn 664, 670, 674
\math_process_auxii:nn .....
..... 664, 678, 680, 682
\math_split:n .....
..... 1313, 1334
\math_split_at_nl:NN .....
..... 1261, 1261, 1349, 1371
\math_split_at_nl_aux:nnNN ...
..... 1264, 1276
\math_split_at_nl_first:w ...
..... 1263, 1266, 1335
\math_split_check_count_-
begins:nnnn ..... 1298, 1308
\math_split_chk_if_begin:ww ...
..... 1271, 1282
\math_split_cleanup_begin_q_-
nil:w ..... 1289, 1294
\math_split_collect_one_end:w ...
..... 1288, 1296, 1318
\math_split_count_begins:n ...
..... 1299, 1302
\math_split_count_begins:w ...
..... 1303, 1305, 1306
\math_split_final_cleanup:nn ...
..... 1312, 1321
\math_split_final_cleanup:w ...
..... 1323, 1327, 1331
\math_split_guard:n 1313, 1324, 1327
\math_tag_dollardollar_-
display_end: ..... 717, 1080
\math_tag_if_mathstyle:nn ...
..... 385, 385, 394
\mathchoice ..... 18, 19
\mathstyle ..... 382
\maybestartnewformulatag .....
..... 1230, 1248, 1256, 1344, 1388
\MaybeStop ..... 8
\MC (plug) ..... 411
\meaning ..... 633, 1350, 1351, 1372, 1373
\mml ..... 11, 343
mode commands:
\mode_if_math:TF 131, 1015, 1025, 1048
\mode_if_vertical:TF ..... 958
msg commands:
\msg_new:nnn ..... 235, 240
\msg_note:nnnn ..... 214, 218, 226
\msg_warning:nn ..... 229

```

N	\renewenvironment . . . . .
	... 1124, 1147, 1152, 1157, 1162,
	1167, 1172, 1177, 1182, 1187, 1193
\newif . . . . .	1345
\nonumber . . . . .	1140, 1226, 1237
\normalfont . . . . .	1217, 1221
O	\result . . . . .
	1346,
\omit . . . . .	1241
On (plug) . . . . .	99, 295
\or . . . . .	157, 172, 187, 193, 198
P	\resulttitle . . . . .
para commands:	1360, 1364, 1380, 1383
\para_raw_end: . . . . .	721, 986
pdf commands:	
\pdf_name_from_unicode_e:n . . . . .	341
pdfdict commands:	
\pdfdict_put:nnn . . . . .	60, 338, 339
pdffile commands:	
\pdffile_embed_stream:nnN . . . . .	61
pdfmanagement commands:	
\pdfmanagement_add:nnn . . . . .	63
peek commands:	
\peek_meaning:NTF . . . . .	758
\peek_remove_spaces:n . . . . .	756
\penalty . . . . .	725
Plugs:	
actual+source . . . . .	495
alt+source . . . . .	510
default . . . . .	419, 441, 450, 528, 613
MC . . . . .	411
On . . . . .	99, 295
single . . . . .	628
test-mathml . . . . .	551
\postdisplaypenalty . . . . .	37, 725, 1079
property commands:	
\property_new:nnnn . . . . .	384
\property_record:nn . . . . .	390
\property_ref:nn . . . . .	391
\ProvidesFile . . . . .	3
Q	S
quark commands:	
\q_nil . . . . .	1263,
1271, 1283, 1294, 1303, 1324, 1335	
\quark_if_nil:nTF . . . . .	1268, 1285, 1306, 1329
R	scan commands:
\RegisterFamilyMapping . . . . .	258, 259
\RegisterMathEnvironment . . . . .	3, 8, 835
\relax . . . . .	1227
\RenewDocumentEnvironment . . . . .	
	\setbox . . . . .
	188
	\show . . . . .
	1341
	\ShowTagging . . . . .
	720, 956, 957, 981, 985, 989
	single (plug) . . . . .
	628
	skip commands:
	\skip_new:N . . . . .
	15
	\skip_set:Nn . . . . .
	1077, 1078
	\skip_vertical:n . . . . .
	726
	skip internal commands:
	\l__math_tmpa_skip . . . . .
	9, 15, 723, 726
	socket commands:
	\socket_assign_plug:nn . . . . .
	... 525, 549, 550, 626, 627, 643,
	644, 645, 646, 647, 648, 649, 650,
	654, 655, 656, 657, 658, 659, 660, 661
	\socket_new:nn . . . . .
	98,
	294, 407, 408, 409, 410, 437, 438,
	439, 440, 494, 526, 527, 611, 612, 640
	\socket_new_plug:nnm . . . . .
	... 99, 295, 411, 415, 419,
	430, 441, 445, 450, 460, 495, 510,
	528, 544, 554, 605, 613, 617, 628, 636
	\socket_use:n . . . . .
	423, 424,
	426, 428, 434, 435, 454, 455, 456,
	458, 464, 465, 586, 587, 712, 724, 988
	\socket_use:nn . . . . .
	713, 979
	Sockets:
	tagsupport/math/content . . . . .
	494
	tagsupport/math/display/begin . .
	437
	tagsupport/math/display/end . .
	437
	tagsupport/math/display/formula/begin
	... 437
	tagsupport/math/display/formula/end
	... 437
	tagsupport/math/end . . . . .
	640
	tagsupport/math/inline/begin . .
	407
	tagsupport/math/inline/end . .
	407
	tagsupport/math/inline/formula/begin
	... 407
	tagsupport/math/inline/formula/end
	... 407

tagsupport/math/mathml/write ..	<a href="#">294</a>
tagsupport/math/mathml/write/prepare .....	<a href="#">98</a>
tagsupport/math/struct/begin ..	<a href="#">526</a>
tagsupport/math/struct/end ..	<a href="#">526</a>
tagsupport/math/substruct/begin ..	<a href="#">611</a>
tagsupport/math/substruct/end ..	<a href="#">611</a>
\space .....	<a href="#">4, 5, 1360, 1380</a>
split commands:	
\split:n .....	<a href="#">1340</a>
\splitnl .....	<a href="#">1338</a>
\splitnl internal commands:	
\_\_splitnl\_aux:nnNN .....	<a href="#">1342</a>
str commands:	
\c\_backslash\_str .....	<a href="#">108</a>
\str\_case:nn .....	<a href="#">210</a>
\str\_if\_eq:nnTF .....	<a href="#">968</a>
\str\_mdfive\_hash:n .....	<a href="#">551, 560</a>
\str\_new:N .....	<a href="#">16</a>
\str\_replace\_all:Nnn .....	<a href="#">102, 103</a>
\str\_set:Nn .....	<a href="#">101</a>
str internal commands:	
\l\_math\_tmpa\_str .....	<a href="#">9, 16, 101, 102, 103, 110</a>
\symletters .....	<a href="#">259</a>
\symsymbols .....	<a href="#">258</a>
sys commands:	
\sys\_if\_engine\_luatex:TF .....	<a href="#">116</a>
\c\_sys\_jobname\_str .....	<a href="#">52, 262, 315</a>
<b>T</b>	
\tabcolsep .....	<a href="#">1100</a>
tag commands:	
\tag\_if\_active:TF .....	<a href="#">24, 663, 966</a>
\tag\_mc\_begin:n .....	<a href="#">634</a>
\tag\_mc\_begin\_pop:n .....	<a href="#">418</a>
\tag\_mc\_end: .....	<a href="#">26, 639</a>
\tag\_mc\_end\_push: .....	<a href="#">26, 414</a>
\tag\_socket\_use:n .....	<a href="#">697, 700, 701</a>
\tag\_socket\_use:nn .....	<a href="#">698</a>
\tag\_start: .....	<a href="#">392</a>
\tag\_stop: .....	<a href="#">392, 1198</a>
\tag\_struct\_begin:n .....	<a href="#">4, 535, 591</a>
\tag\_struct\_end: .....	<a href="#">29, 547, 609</a>
tag internal commands:	
\_\_tag\_check\_para\_end\_show:nn .....	<a href="#">28</a>
\_\_tag\_gincr\_para\_end\_int: .....	<a href="#">27</a>
\l\_tag\_math\_alt\_bool .....	<a href="#">11, 42, 398, 569</a>
\_\_tag\_math\_disable: .....	<a href="#">641, 641</a>
\_\_tag\_math\_enable: .....	<a href="#">652, 652, 663</a>
\g\_tag\_math\_luamml\_tl .....	<a href="#">11, 43, 44, 210, 289, 290</a>
\g\_tag\_math\_mathml\_AF\_bool .....	<a href="#">11, 40, 252, 309, 350, 357</a>
\l\_tag\_math\_mathml\_AF\_bool .....	<a href="#">11, 39, 402, 574, 596</a>
\l\_tag\_math\_mathml\_files\_clist .....	<a href="#">11, 50, 51, 344, 397</a>
\l\_tag\_math\_mathml\_pane\_bool .....	<a href="#">11, 41, 62, 399</a>
\l\_tag\_math\_texsource\_AF\_bool .....	<a href="#">11, 37, 404, 532, 588</a>
\l\_tag\_math\_texsource\_pane\_bool .....	<a href="#">11, 38, 401</a>
\l\_tag\_para\_main\_tag\_tl .....	<a href="#">968</a>
\g\_tag\_struct\_tag\_tl .....	<a href="#">964, 968</a>
\_\_tag\_tool\_close\_P: .....	<a href="#">22, 22, 444, 977</a>
\tagmcbegin .....	<a href="#">1220, 1222, 1367, 1386</a>
\tagmcend .....	<a href="#">621, 1219, 1222, 1394</a>
\tagpdfparaOff .....	<a href="#">980</a>
\tagpdfparaOn .....	<a href="#">722, 987</a>
\tagpdfsetup .....	<a href="#">33, 246, 248</a>
\tagstructbegin .....	<a href="#">1219, 1361, 1381</a>
\tagstructend .....	<a href="#">623, 1222, 1395</a>
tagsupport/math/content (socket) .....	<a href="#">494</a>
tagsupport/math/display/begin (socket) .....	<a href="#">437</a>
tagsupport/math/display/end (socket) .....	<a href="#">437</a>
tagsupport/math/display/formula/begin (socket) .....	<a href="#">437</a>
tagsupport/math/display/formula/end (socket) .....	<a href="#">437</a>
tagsupport/math/end (socket) .....	<a href="#">640</a>
tagsupport/math/inline/begin (socket) .....	<a href="#">407</a>
tagsupport/math/inline/end (socket) .....	<a href="#">407</a>
tagsupport/math/inline/formula/begin (socket) .....	<a href="#">407</a>
tagsupport/math/inline/formula/end (socket) .....	<a href="#">407</a>
tagsupport/math/mathml/write (socket) .....	<a href="#">294</a>
tagsupport/math/mathml/write/prepare (socket) .....	<a href="#">98</a>
tagsupport/math/struct/begin (socket) .....	<a href="#">526</a>
tagsupport/math/struct/end (socket) .....	<a href="#">526</a>
tagsupport/math/substruct/begin (socket) .....	<a href="#">611</a>
tagsupport/math/substruct/end (socket) .....	<a href="#">611</a>
tbl commands:	
\tbl\_crcr:n .....	<a href="#">125</a>
\tbl\_restore\_outer\_cell\_data: .....	<a href="#">129</a>
test-mathml (plug) .....	<a href="#">551</a>
TeX and L <sup>A</sup> T <sub>E</sub> X 2 $\varepsilon$ commands:	
\@addtopreamble .....	<a href="#">140</a>
\@arrayright .....	<a href="#">132</a>
\@badmath .....	<a href="#">1016, 1027, 1040, 1043</a>
\@chnum .....	<a href="#">141</a>
\@classx .....	<a href="#">137</a>

```

\@classz ..... 135
\@currenvir ..... 945
\@currenvline ..... 946
\@doendpe ..... 728
\@eha ..... 944
\@endpbox ..... 190, 196, 201
\@endpfalse ..... 951
\@endptrue ..... 990
\@ensuredmath ..... 1052, 1056
\@eqnswtrue ..... 1232, 1250
\@execute@begin@hook ..... 947
\@ifpackage{loaded} ..... 223
\@ifundefined ..... 943
\@ignorefalse ..... 949
\@iiiparbox ..... 7
\@kernel@after@begindocument . 1115
\@kernel@before@begindocument ...
..... 1000, 1029, 1111, 1122
\@kernel@math@registered@begin ...
..... 856, 890, 923, 955
\@kernel@math@registered@end 934, 984
\@latex@error ..... 944
\@lign ..... 1244
\@namedef ..... 1214, 1225, 1236, 1254
\@ne . 1158, 1163, 1173, 1178, 1233, 1239
\@nextchar ..... 188, 194, 199
\@preamble ..... 133
\@startpbox ..... 188, 194, 199
\@subformulasfalse ..... 1355
\@subformulastrue ..... 1359
\@tabarray ..... 1103
\@tabular ..... 1091, 1093
\@tempcnta ..... 138
\@xp ..... 1195
\add@amps ..... 1240
\align@ ..... 1119
\alignsep@ ..... 1242
\ar@align@mcell ..... 191
\ar@mcellbox ..... 188
\black@ ..... 1131, 1135
\col@sep ..... 1100
\common@align@ending ...
..... 1134, 1150, 1155, 1160,
..... 1165, 1170, 1175, 1180, 1185, 1190
\count@ ..... 138
\cr ..... 29, 30
\d@llarbegin ...
..... 144, 145, 159, 160, 175, 176, 1100
\d@llarend ...
..... 147, 152, 162, 167, 178, 183, 1101
\do@row@strut ...
..... 155, 170, 186, 192, 197, 202
\gather@ ..... 1119
\halign ..... 30
\if@eqnsw ..... 1238
\if@subformulas ..... 622, 1345, 1389
\ifingather@ ..... 1137
\ifmeasuring@ ... 3, 8, 1198, 1216, 1390
\ifst@rred ..... 1226, 1232, 1237, 1250
\iftag@ ..... 1243
\iftagsleft@ ..... 1195
\insert@column ...
..... 146, 150, 161, 165, 177, 181
\insert@pcolumn ..... 189, 195, 200
\lendmultline@ ..... 1195
\lineht@ ..... 1251
\m@ne ..... 1173, 1178, 1183, 1188
\m@th 7–9, 27, 38, 668, 1105, 1217, 1221
\make@display@tag ..... 1228, 1244
\math@cr ..... 1131, 1135
\maxfields@ ..... 1240
\measuring@true ..... 1198
\multline@ ..... 1119
\on@line ..... 946
\place@tag ..... 1245
\prepnext@tok ..... 139, 205
\rendmultline@ ..... 1195
\reserved@a ..... 944, 945, 952
\restore@math@cr ..... 1254, 1259
\restorealignstate@ ..... 1138
\row@ ..... 1233, 1239
\setboxz@h ..... 1244
\split@tag ..... 38
\st@rredfalse .. 1148, 1158, 1173, 1183
\st@rredtrue ..... 1125,
..... 1153, 1163, 1168, 1178, 1188, 1193
\start@align ... 1148, 1153, 1158,
..... 1163, 1168, 1173, 1178, 1183, 1188
\start@gather ..... 1125
\start@multline ..... 1193
\strut@ ..... 1244
>tag@true ..... 1238
\textonly@unskip ..... 803
\totwidth@ ..... 1131, 1135
\tw@ ..... 1168, 1183, 1188
\z@ ..... 1148, 1153, 1251
tex commands:
\text_cr:D ..... 814
\text_everydisplay:D ..... 1072, 1074
\text_everymath:D ..... 1062, 1064
\text_the:D ..... 1064, 1074
\text ..... 18
tl commands:
\c_space_tl ..... 108, 368,
..... 370, 372, 374, 376, 472, 474, 476, 789
\tl_clear:N ..... 534, 590, 751
\tl_const:Nn ..... 80, 88, 94, 479

```

\tl_gput_right:Nn . . . . .	1000, 1029, 1111, 1115, 1122
\tl_gset:Nn . . . . .	44, 289, 290, 676, 677, 1278, 1279
\tl_gset_eq:NN . . . . .	65
\tl_if_blank:nTF . . . . .	709, 734
\tl_if_blank_p:n . . . . .	691
\tl_if_empty:NTF . . . . .	266, 1352, 1374, 1392
\tl_if_eq:NNTF . . . . .	482
\tl_if_eq:NnTF . . . . .	562
\tl_if_exist:NTF . . . . .	57, 310, 571
\tl_if_in:NnTF . . . . .	1091
\tl_if_in:nnTF . . . . .	668
\tl_map_inline:nn . . . . .	803
\tl_new:N . . . . .	12, 13, 14, 17, 18, 19, 20, 21, 32, 43, 64, 87, 467, 478, 552, 553, 746, 824, 1346
\tl_put_right:Nn . . . . .	767
\tl_set:Nn . . . . .	104, 468, 480, 499, 503, 507, 508, 514, 518, 522, 523, 559, 564, 567, 570, 837, 871, 904, 1262, 1340
\tl_set_eq:NN . . . . .	533, 561, 589
\tl_to_str:n . . . . .	246, 248
\tl_trim_spaces_apply:nN . . . . .	670
tl internal commands:	
\l_math_attribute_class_tl . . . . .	32, 564, 567, 594
\l_math_content_actual_tl . . . . .	10, 18, 499, 523, 540
\l_math_content_AF_mathml_tl . . . . .	21, 507, 522
\l_math_content_AF_source_tl . . . . .	19, 101, 503, 518, 533, 560, 589
\l_math_content_AF_source_tmpa_tl . . . . .	20, 533, 534, 538, 589, 590, 600
\l_math_content_AF_tl . . . . .	10
\l_math_content_alt_tl . . . . .	10, 17, 508, 514, 541, 570, 602
\l_math_content_hash_tl . . . . .	112, 552, 559, 571, 577, 580, 584, 598
\l_math_content_template_tl . . . . .	21, 467, 468, 501, 516
\l_math_env_name_tl . . . . .	31, 824, 830, 837, 871, 904
\g_math_grabbed_env_tl . . . . .	9, 22, 23, 12, 471, 475, 482, 489, 491, 539, 562, 601, 676, 1360, 1380
\g_math_grabbed_math_tl . . . . .	9, 22, 23, 13, 473, 485, 490, 561, 633, 677, 1349, 1351, 1352, 1371, 1373, 1374, 1392
\l_math_grabbed_math_tl . . . . .	553, 561
\l_math_grabbed_tl . . . . .	29, 746, 751, 767, 822
\c_math_inline_env_tl . . . . .	479, 482
\c_math_mathml_write_after_tl . . . . .	80, 272, 301
\l_math_mathml_write_before_tl . . . . .	80, 104, 266, 270, 299
\c_math_mathml_write_final_tl . . . . .	80, 281, 326
\c_math_mathml_write_init_tl . . . . .	80, 263, 319
\l_math_texsource_template_tl . . . . .	22, 478, 480, 505, 520
\l_math_tmpa_tl . . . . .	9, 14, 61, 63, 65, 1262, 1264, 1340, 1341, 1342
token commands:	
\token_to_str:N . . . . .	773, 776, 778, 784, 789, 790, 791, 805
\tracingall . . . . .	859, 893, 926
\tracingnone . . . . .	863, 896
\typeout . . . . .	348, 353, 359, 577, 580, 584, 632, 633, 719, 743, 846, 849, 880, 883, 913, 916, 933, 957, 964, 970, 976, 981, 985, 989, 1076, 1215, 1350, 1351, 1354, 1358, 1372, 1373, 1376, 1379, 1402
U	
\unskip . . . . .	803
use commands:	
\use_ii_i:nn . . . . .	1316
\UseHook . . . . .	942
\UseTaggingSocket . . . . .	128, 1095
V	
\vbox . . . . .	188, 199
\vcenter . . . . .	7
\vtop . . . . .	194