The HEP-TITLE package*

Extensions for the title page

Jan Hajer[†] 2023/07/01

Abstract

The HEP-TITLE package extends the title macros of the standard classes with macros for a preprint, affiliation, editors, and endorsers.

To use the HEP-TITLE package include it with \usepackage{hep-title}.

Most macros are intended for the use in the preamble. They are implemented using the TITLING [1] and AUTHBLK [2] packages.

1 Macros

If the hyperref package is loaded the portable document format meta information is set according to the $\{\langle text \rangle\}$ and $\{\langle text \rangle\}$ information.

1.1 Title

\series

\title

The \series{ $\langle series \rangle$ } places a series title above the usual title generated via \title{ $\langle title \rangle$ }. The \subtitle{ $\langle subtitle \rangle$ } macro places a subtitle below the usual title. The fonts and their size can be adjusted using the \seriesfont{ $\langle font \rangle$ }, \titlefont{ $\langle font \rangle$ }, and \subtitlefont{ $\langle font \rangle$ } macros.

In order to facilitate multiple authors with different affiliations the AUTHBLK package [2] is extended. The author macro is extended to take a affiliation label $\author(\langle label\rangle) \{\langle name \rangle\}$. The

affiliation macro takes the corresponding label $\alpha[\langle label \rangle] \{\langle institution \rangle\}$. Additionally, the $\alpha[\langle label \rangle] \{\langle institution \rangle\}$.

The fonts can be adjusted using the \authorfont{ $\langle font \rangle$ } and \affiliationfont{ $\langle font \rangle$ } macros.

\subtitle

\seriesfont 1.2 Authors

\titlefont

\subtitlefont

\author

\authorfont \email

\affiliation

\affiliationfont

\author[affil1]{Author one \email{email one}}

The following lines add e.g. two authors with different affiliations

\affiliation[affil1]{Affiliation one}

\author[affil2]{Author two \email{email two}}\affiliation[affil1,affil2]{Affiliation two}

\editor Additionally the \editor[$\langle label \rangle$]{ $\langle name \rangle$ } and \endorser[$\langle label \rangle$]{ $\langle name \rangle$ } macros are provided that act similar to the \author[$\langle label \rangle$]{ $\langle name \rangle$ } macros but place their content in a dedicated line. Their font can be adjusted by the \editorfont{ $\langle font \rangle$ } and \endorserfont{ $\langle font \rangle$ }. \editorfont The titles of these lines can be adjusted using the \editortitle{ $\langle singluar \rangle$ }{ $\langle plural \rangle$ } and

\endorserfont *This document corresponds to HEP-TITLE V1.2.

\editortitle ^{†jan.hajer@tecnico.ulisboa.pt}

\endorsertitle

\editortitlefont

\endorsertitlefont

1.3 Abstract

abstract (env.) The abstract environment is adjusted to not start with an indentation. The abstract* environment takes care of placing the title as well. This is used in twocolumn documents if the abstract should span both columns.

1.4 Preprint

\preprint \preprintfont

The \prescript{numer} macro places a pre-print number in the upper right corner of the title page. The $\prescript{preprintfont}$ macro can be used to change the font of the preprint.

References

- [1] P. R. Wilson. 'The titling package: Control over the typesetting of the \maketitle command' (2000). CTAN: titling.
- [2] P. W. Daly. 'A LATEX Package to Prepare Author and Affiliation Blocks: Support for footnote style author/affiliation' (2001). CTAN: authblk.